

ISO/TS 21139-21:2019 (E)

Permanence and durability of commercial prints — Part 21: In-window display — Light and ozone stability

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Use profile |
| 4.1 | General |
| 4.2 | Environmental light condition |
| 4.3 | Environmental ozone condition |
| 5 | Test method |
| 5.1 | General |
| 5.2 | Sample preparation |
| 5.2.1 | Outline |
| 5.2.2 | Test target |
| 5.2.3 | Storage conditions between printing and light or ozone exposure test |
| 5.2.4 | Reference samples |
| 5.2.5 | Backing of the specimens |
| 5.3 | Light exposure |
| 5.3.1 | Outline |
| 5.3.2 | Spectral power distribution |
| 5.3.3 | Light intensity |
| 5.3.4 | Temperature and humidity |
| 5.3.5 | Duration of the light exposures |
| 5.4 | Ozone test |
| 5.4.1 | Outline |
| 5.4.2 | Apparatus |
| 5.4.3 | Test procedure |
| 5.4.4 | Test conditions |
| 5.4.4.1 | General |
| 5.4.4.2 | Ozone concentration |
| 5.4.4.3 | Temperature and humidity |
| 5.4.4.4 | Duration of the ozone exposures |
| 6 | Measurement |
| 6.1 | General |
| 6.2 | Measurement conditions |
| 6.3 | Calculation of colour difference |
| 7 | Data analysis |
| 7.1 | General |
| 7.2 | Image quality parameter for data analysis |
| 7.3 | Environmental conditions |
| 7.4 | Estimation of time to reach certain change |
| 8 | Reporting |
| Annex A | (informative) Display window type and lighting design |

- A.1 Type of display windows**
- A.2 Lighting design**
- A.3 Air conditioning (ozone, temperature and humidity control)**

Annex B (informative) Example of test results

- B.1 Outline**
- B.2 Light exposure test**
 - B.2.1 Samples**
 - B.2.2 Test procedures**
 - B.2.3 Test results**
- B.3 Evaluation**
 - B.3.1 Image quality parameter**
 - B.3.2 Visual assessment**
 - B.3.3 Correspondence of measurements to the visual assessments**
 - B.3.4 Estimation of the time to reach certain change**

Page count: 14