

DIN 15765:2020-11 (E)

Entertainment Technology - Multi-core cable systems for mobile productions and entertainment technology

| Contents | Page |
|--|------|
| Foreword | 4 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions..... | 7 |
| 4 Types | 8 |
| 4.1 General | 8 |
| 4.2 Power class..... | 8 |
| 4.3 Number of circuits | 8 |
| 4.4 Connectors and contact assignment..... | 9 |
| 4.4.1 General | 9 |
| 4.4.2 Types and contact assignment for different connectors | 9 |
| 5 Requirements for connectors..... | 11 |
| 5.1 General requirements | 11 |
| 5.2 Particular requirements | 12 |
| 6 Requirements for plugboxes | 12 |
| 7 Cables | 12 |
| 7.1 General | 12 |
| 7.2 Requirements for the insulating material..... | 13 |
| 7.3 Conductor cross-section..... | 13 |
| 7.4 Cable length..... | 13 |
| 8 Electrical safety..... | 13 |
| 8.1 General | 13 |
| 8.2 Personal protection..... | 14 |
| 8.3 Cable protection | 14 |
| Annex A (normative) Criteria for the dimensional accuracy of type D | 15 |
| Annex B (informative) Permitted cable lengths for PVC or rubber cables | 16 |
| Annex C (informative) Criteria for the configurations of connectors | 17 |
| C.1 Configurations of connectors in multi-core cable systems | 17 |
| C.1.1 General | 17 |
| C.1.2 Configuration 1 | 17 |
| C.1.3 Configuration 2 | 18 |
| Bibliography | 20 |

Figures

| | |
|---|----|
| Figure A.1 — Types and dimensions..... | 15 |
| Figure C.1 — Multi-core cable system, configuration 1 | 17 |
| Figure C.2 — Multi-core cable system, configuration 2 A | 18 |
| Figure C.3 — Multi-core cable system, configuration 2 B | 19 |

Tables

| | |
|---|-----------|
| Table 1 — Power classes..... | 8 |
| Table 2 — Number of circuits..... | 8 |
| Table 3 — Types and contact assignment for the different connectors..... | 9 |
| Table 4 — Minimum cross-sections | 13 |
| Table B.1 — Permitted threshold lengths in the TN system; 400/230 V 50 Hz (excerpt from DIN VDE 0100 Supplement 5:2017-10, Table A21)..... | 16 |
| Table B.2 — Permitted threshold lengths in the TN system; 400/230 V 50 Hz (excerpt from DIN VDE 0100 Supplement 5:2017-10, Table A22)..... | 16 |