

ISO 15739:2023-04 (E)

Photography - Electronic still-picture imaging - Noise measurements

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Test conditions | 3 |
| 4.1 | General | 3 |
| 4.2 | Illumination | 4 |
| 4.2.1 | Characteristics | 4 |
| 4.2.2 | Daylight illumination | 4 |
| 4.2.3 | Tungsten illumination | 4 |
| 4.2.4 | Uniformity of illumination and reflection test chart illumination geometry | 4 |
| 4.2.5 | Light source amplitude variations | 4 |
| 4.3 | Temperature and relative humidity | 4 |
| 4.4 | White balance | 5 |
| 4.5 | Infrared (IR) blocking filter | 5 |
| 4.6 | Photosite integration time | 5 |
| 4.7 | Compression | 5 |
| 5 | Noise measurement procedures | 5 |
| 5.1 | General | 5 |
| 5.2 | Measurement of a DSC using a test chart | 5 |
| 5.2.1 | General | 5 |
| 5.2.2 | OECF measurement | 5 |
| 5.2.3 | Adjustment of illumination | 6 |
| 5.2.4 | Test chart | 6 |
| 5.2.5 | Non-uniformity and image structure spatial components | 6 |
| 5.2.6 | Camera lens focus | 6 |
| 5.3 | Measurement of a DSC having manual exposure control | 7 |
| 5.3.1 | General | 7 |
| 5.3.2 | OECF measurement | 7 |
| 5.3.3 | Adjustment of illumination | 8 |
| 5.3.4 | Test densities | 8 |
| 5.3.5 | Diffuser setting | 8 |
| 5.3.6 | Camera lens focus | 8 |
| 5.4 | Measurement of a DSC having a removable lens | 9 |
| 5.4.1 | General | 9 |
| 5.4.2 | OECF measurement | 9 |
| 5.4.3 | Adjustment of illumination | 9 |
| 5.4.4 | Test densities | 9 |
| 6 | Calculation of metrics | 10 |
| 6.1 | General | 10 |
| 6.2 | Noise | 10 |
| 6.2.1 | General | 10 |
| 6.2.2 | Determining the noise for luminance measurements | 11 |
| 6.2.3 | Determining the noise for exposure measurements | 12 |

| | | |
|--|---|----|
| 6.3 | Signal-to-noise ratios -- large area | 12 |
| 6.3.1 | General | 12 |
| 6.3.2 | Determining the reference luminance and luminance value for calculating signal-to-noise ratio | 12 |
| 6.3.3 | Determining the signal-to-total noise ratio | 13 |
| 6.3.4 | Determining the temporal signal-to-noise ratio | 14 |
| 6.3.5 | Determining the fixed pattern signal-to-noise ratio | 14 |
| 6.3.6 | Determining the exposure values and the signal-to-noise ratios for exposure measurements | 15 |
| 6.4 | DSC dynamic range | 15 |
| 6.4.1 | General | 15 |
| 6.4.2 | Determining the DSC dynamic range for luminance measurements | 15 |
| 6.4.3 | Determining the DSC dynamic range for exposure measurements | 17 |
| 7 | Presentation of results | 17 |
| 7.1 | General | 17 |
| 7.2 | Signal-to-noise ratios | 17 |
| 7.3 | DSC dynamic range | 17 |
| Annex A (normative) Noise component analysis | | 18 |
| Annex B (normative) Visual noise measurements | | 24 |
| Annex C (normative) Removing low frequency variations from the image signals | | 34 |
| Annex D (informative) Procedure for determining signal-to-noise ratio | | 35 |
| Annex E (informative) Practical viewing conditions for various output media | | 37 |
| Annex F (informative) Introduction of perceptually uniform mapping of visual noise to noisiness JND | | 38 |
| Bibliography | | 41 |