

ISO/TS 21139-22:2023-05 (E)

Permanence and durability of commercial prints - Part 22: Backlit display in indoor or shaded outdoor conditions - Light stability

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
3.1	Measures of exposure severity	2
3.2	Exposure conditions	2
3.3	Abbreviations	3
4	Use profile	4
4.1	General	4
4.2	Parameters of backlit display	4
4.3	Frontside exposure and environmental conditions	6
4.4	Equivalent test conditions	6
4.4.1	Severity weighted exposure condition	6
4.4.2	Equivalent test duration	8
4.5	Relevance of use	9
5	Test methods	10
5.1	General	10
5.2	Sample preparation	10
5.2.1	Outline	10
5.2.2	Test target	10
5.2.3	Sample labelling and marking	10
5.2.4	Storage conditions between printing and light exposure test	11
5.2.5	Reference samples	11
5.2.6	Backing of the specimens	11
5.3	Light exposure	11
5.3.1	Test method and filter condition	11
5.3.2	Light intensity	11
5.3.3	Temperature and humidity	11
5.3.4	Duration of the light exposure	12
5.4	Exposure of the frontside of the print	12
5.4.1	Specimen mounting for frontside exposure	12
5.4.2	Duration of the frontside exposure	12
5.5	Exposure of the backside of the print	12
5.5.1	Specimen mounting for backside exposure	12
5.5.2	Duration of the backside exposure	12
6	Measurement	12
6.1	General	12
6.2	Measurement conditions	13
7	Data analysis	14
7.1	General	14
7.2	Image quality parameter for data analysis	14
7.3	Equivalent test conditions	14

7.4	Estimation of time to reach certain change	14
8	Test report	15
	Annex A (normative) Relative severity of the relative spectral irradiance	17
	Annex B (normative) Characterization of an example LED light box	21
	Annex C (informative) sRGB test target	25
	Annex D (informative) Overview of test conditions in backlit context	26
	Bibliography	27