

ISO 18946:2023-12 (E)

Imaging materials - Reflection colour photographic prints - Method for testing humidity fastness

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Requirements | | 2 |
| 5 Outline of test procedure | | 2 |
| 6 Sample preparation | | 3 |
| 6.1 General..... | | 3 |
| 6.2 Test target..... | | 4 |
| 6.3 Printer driver setting..... | | 5 |
| 6.4 Printing conditions..... | | 5 |
| 6.5 Sample conditioning..... | | 5 |
| 7 Humidity exposure | | 6 |
| 7.1 Equipment and calibration..... | | 6 |
| 7.2 Test environment control..... | | 6 |
| 7.3 Method A — Fixed humidity condition..... | | 7 |
| 7.4 Method B — Multiple humidity conditions..... | | 7 |
| 8 Colorimetric measurement | | 7 |
| 9 Data analysis | | 8 |
| 10 Test report | | 9 |
| 10.1 General..... | | 9 |
| 10.2 Samples information..... | | 9 |
| 10.3 Test conditions..... | | 9 |
| 10.4 Results..... | | 9 |
| 10.4.1 General..... | | 9 |
| 10.4.2 Method A..... | | 10 |
| 10.4.3 Method B..... | | 10 |
| Annex A (informative) Correspondence to psychophysical evaluation | | 11 |
| Annex B (informative) Test target for humidity fastness test — RGB values of input signal in 8 bit | | 12 |
| Bibliography | | 13 |