

# ISO 14649-10:2004-12 (E)

## Industrial automation systems and integration - Physical device control - Data model for computerized numerical controllers - Part 10: General process data

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | v           |
| Introduction ..... |  | vi          |
| 1                  | Scope .....  | 1           |
| 2                  | Normative references .....                                 | 1           |
| 3                  | Terms and definitions .....                                | 2           |
| 4                  | General Process data .....                                 | 3           |
| 4.1                | Header and references .....                                | 3           |
| 4.2                | General types and definitions .....                        | 4           |
| 4.2.1              | Measure units .....  | 4           |
| 4.2.2              | Other general types .....                                  | 6           |
| 4.3                | Where to start: Project .....                              | 6           |
| 4.3.1              | Person and address .....                                   | 7           |
| 4.4                | What to machine: Workpiece and manufacturing feature ..... | 7           |
| 4.4.1              | Workpiece .....  | 7           |
| 4.4.2              | Manufacturing feature .....                                | 9           |
| 4.5                | Catalogue of manufacturing features .....                  | 10          |
| 4.5.1              | Region .....   | 10          |
| 4.5.2              | Two5D manufacturing feature .....                          | 12          |
| 4.5.3              | Machining feature .....                                    | 12          |
| 4.5.4              | Planar face .....  | 13          |
| 4.5.5              | Pocket .....   | 14          |
| 4.5.6              | Slot .....   | 17          |
| 4.5.7              | Step .....   | 21          |
| 4.5.8              | Profile feature .....                                      | 22          |
| 4.5.9              | Round hole .....   | 27          |
| 4.5.10             | Toolpath feature .....                                     | 31          |
| 4.5.11             | Boss .....   | 31          |
| 4.5.12             | Spherical cap .....  | 32          |
| 4.5.13             | Rounded end .....  | 33          |
| 4.5.14             | Compound feature .....                                     | 33          |
| 4.5.15             | Replicate feature .....                                    | 35          |
| 4.5.16             | Transition feature .....                                   | 40          |
| 4.5.17             | Thread .....   | 42          |
| 4.5.18             | Profile .....  | 45          |
| 4.5.19             | Travel path .....  | 52          |
| 4.5.20             | Surface texture parameter .....                            | 53          |
| 4.6                | To make things happen: Executables .....                   | 54          |
| 4.6.1              | Executable .....   | 54          |
| 4.6.2              | Workingstep .....  | 55          |
| 4.6.3              | NC function .....  | 61          |
| 4.6.4              | Program structure .....                                    | 62          |
| 4.7                | How to machine: Operations .....                           | 71          |
| 4.7.1              | Operation .....  | 72          |
| 4.7.2              | Machining operation .....                                  | 73          |
| 4.8                | To be in full control: Explicit toolpath definition .....  | 76          |
| 4.8.1              | Toolpath .....   | 76          |

|       |   |     |
|-------|---|-----|
| 4.8.2 | Feedstop .....  | 79  |
| 4.8.3 | Trajectory .....  | 79  |
| 4.8.4 | Cutter location trajectory .....                                      | 79  |
| 4.8.5 | Cutter contact trajectory .....                                       | 80  |
| 4.8.6 | Axis trajectory .....   | 81  |
| 4.8.7 | Parameterised path .....  | 82  |
| 4.8.8 | Connector .....   | 82  |
| 4.8.9 | Approach and lift path .....  | 83  |
| 4.9   | Rules .....   | 85  |
| 4.9.1 | dependent_instantiable_representation_item .....                      | 85  |
| 4.9.2 | dependent_instantiable_shape_representation .....                     | 85  |
| 4.9.3 | geometric_representation_item_3d .....                                | 86  |
| 4.10  | End of schema .....   | 86  |
| 5     | Conformance requirements .....  | 86  |
| 5.1   | Conformance class 1 entities .....                                    | 87  |
| 5.2   | Conformance class 2 entities .....                                    | 87  |
| 5.3   | Conformance class 3 entities .....                                    | 89  |
| 5.4   | Conformance class 4 entities .....                                    | 91  |
| 5.5   | Conformance class 5 entities .....                                    | 93  |
| 5.6   | Conformance class 6 entities .....                                    | 96  |
|       | Annex A (normative) EXPRESS expanded listing .....                    | 99  |
|       | Annex B (normative) Short names of entities .....                     | 125 |
|       | Annex C (normative) Implementation method specific requirements ..... | 133 |
|       | Annex D (informative) EXPRESS-G figures .....                         | 134 |
|       | Annex E (informative) Computer-interpretable listings .....           | 150 |
|       | Index .....   | 151 |