

# ISO 3408-4:2006-06 (E)

## Ball screws - Part 4: Static axial rigidity

---

| Contents   | Page      |
|--|-----------|
| <b>Foreword .....</b>  | <b>iv</b> |
| <b>1 Scope .....</b>   | <b>1</b>  |
| <b>2 Normative references .....</b>  | <b>1</b>  |
| <b>3 Terms and definitions .....</b>   | <b>1</b>  |
| <b>4 Symbols and subscripts .....</b>  | <b>1</b>  |
| <b>4.1 Symbols .....</b>   | <b>1</b>  |
| <b>4.2 Subscripts .....</b>  | <b>2</b>  |
| <b>5 Determination of static axial rigidity, R .....</b>   | <b>3</b>  |
| <b>5.1 General .....</b>   | <b>3</b>  |
| <b>5.2 Static axial rigidity, R .....</b>  | <b>5</b>  |
| <b>5.3 Static axial rigidity of ball screw, R<sub>bs</sub> .....</b>   | <b>5</b>  |
| <b>5.4 Static axial rigidity of ball screw shaft, R<sub>s</sub> .....</b>  | <b>5</b>  |
| <b>5.4.1 General .....</b>   | <b>5</b>  |
| <b>5.4.2 Rigid mounting of ball screw shaft at one end .....</b>   | <b>5</b>  |
| <b>5.4.3 Rigid mounting of ball screw shaft at both ends .....</b>   | <b>6</b>  |
| <b>5.5 Static axial rigidity of ball nut unit, R<sub>nu</sub> .....</b>  | <b>6</b>  |
| <b>5.5.1 Static axial rigidity of ball nut unit with backlash, R<sub>nu1</sub> .....</b>                                   | <b>6</b>  |
| <b>5.5.2 Static axial rigidity of symmetrically preloaded ball nut unit, R<sub>nu2,4</sub> .....</b>                       | <b>10</b> |
| <b>5.5.3 Correction for accuracy, far .....</b>  | <b>12</b> |
| <b>Annex A (informative) Example calculation of static axial rigidity in preloaded symmetrical double nut system .....</b> | <b>14</b> |
| <b>Annex B (informative) Correction for load application, fal .....</b>  | <b>17</b> |