

ISO 3408-5:2006-06 (E)

Ball screws - Part 5: Static and dynamic axial load ratings and operational life

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and subscripts	2
4.1	Symbols	2
4.2	Subscripts	3
5	Basic axial load ratings	4
5.1	Basic static axial load rating, C_{0a}	4
5.2	Basic dynamic axial load rating, C_a	4
6	Modified axial load ratings	5
6.1	Modified static axial load rating, C_{0am}	5
6.1.1	General equation	5
6.1.2	Correction for surface hardness, f_{h0}	5
6.1.3	Correction for accuracy, f_{ac}	6
6.2	Modified dynamic axial load rating, C_{am}	6
6.2.1	General equation	6
6.2.2	Correction for surface hardness, f_h	6
6.2.3	Correction for accuracy, f_{ac}	6
6.2.4	Influence of material melting process, f_m	6
7	Life	7
7.1	Equivalent rotational speed and equivalent axial load	7
7.1.1	General	7
7.1.2	Ball screw with backlash between ball nut and screw shaft	7
7.1.3	Ball screw with preloaded ball nuts on screw shaft	10
7.2	Nominal life, L or L_h	12
7.2.1	Ball screw with backlash between ball nut and screw shaft	12
7.2.2	Ball screw with preloaded ball nuts on screw shaft	13
7.2.3	Resulting life, L_r	13
7.2.4	Nominal life, L_{ar} or L_{har} , with reliability factor, f_{ar} (see Table 3)	13
7.3	Modified life, L_m or L_{hm}	14
7.3.1	Ball screw with backlash between ball nut and screw shaft	14
7.3.2	Ball screw with preloaded ball nuts on screw shaft	14
7.3.3	Modified resulting life, L_{mr}	14
7.3.4	Modified life, L_{mar} or L_{hmar} , with reliability factor, f_{ar} (see Table 3)	14