

ISO/ASTM 52911-2:2019-09 (E)

Additive manufacturing - Design - Part 2: Laser-based powder bed fusion of polymers

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
4.1	Symbols	2
4.2	Abbreviated terms	3
5	Characteristics of powder bed fusion (PBF) processes	3
5.1	General	3
5.2	Size of the parts	3
5.3	Benefits to be considered in regard to the PBF process	4
5.4	Limitations to be considered in regard to the PBF process	4
5.5	Economic and time efficiency	5
5.6	Feature constraints (islands, overhang, stair-step effect)	5
5.6.1	General	5
5.6.2	Islands	5
5.6.3	Overhang	6
5.6.4	Stair-step effect	6
5.7	Dimensional, form and positional accuracy	6
5.8	Data quality, resolution, representation	6
6	Design guidelines for laser-based powder bed fusion of polymers (LB-PBF/P)	7
6.1	General	7
6.2	Material and structural characteristics	7
6.3	Anisotropy of the material characteristics	8
6.4	Build orientation, positioning and arrangement	9
6.4.1	General	9
6.4.2	Powder coating	9
6.4.3	Part location in the build chamber	9
6.4.4	Oversintering	9
6.4.5	Packing parts efficiently in the build chamber	9
6.5	Surface roughness	10
6.6	Post-production finishing	10
6.7	Design considerations	11
6.7.1	Allowing for powder removal	11
6.7.2	Reducing warpage	11
6.7.3	Wall thickness	11
6.7.4	Gaps, cylinders and holes	11
6.7.5	Lattice structures	12
6.7.6	Fluid channels	12
6.7.7	Springs and elastic elements	13
6.7.8	Connecting elements and fasteners	13
6.7.9	Static assemblies	14
6.7.10	Movable assemblies	15

6.7.11	Bearings	15
6.7.12	Joints	15
6.7.13	Integrated markings	16
6.7.14	Cutting and joining	16
6.8	Example applications	17
6.8.1	Functional toy car with integrated spring	17
6.8.2	Robot gripper	18
7	General design consideration	19
	Bibliography	20