

ISO 16573-2:2022-02 (E)

Steel - Measurement method for the evaluation of hydrogen embrittlement resistance of high-strength steels - Part 2: Slow strain rate test

Contents	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Principle.....	1
5 Specimen preparation.....	2
5.1 General.....	2
5.2 Cylindrical type specimen.....	2
5.3 Flat type specimen.....	3
6 Hydrogen charging methods.....	4
6.1 General.....	4
6.2 Cathodic charging.....	4
6.2.1 Hydrogen charging solution.....	4
6.2.2 Hydrogen charging conditions.....	4
6.3 Hydrogen absorption in aqueous solution at free corrosion potential.....	5
6.4 Hydrogen absorption in atmospheric corrosion environments.....	5
6.5 Hydrogen absorption in high pressure hydrogen gas.....	5
7 Preparation of electroplating solution and electroplating condition.....	5
7.1 General.....	5
7.2 Electroplating solution.....	5
7.3 Electroplating conditions.....	6
8 Slow strain rate test.....	6
8.1 General.....	6
8.2 Procedure.....	6
8.3 Presentation of the results.....	7
9 Post-test specimen treatment.....	9
10 Hydrogen thermal desorption.....	10
10.1 General.....	10
10.2 Experimental apparatus (gas chromatograph).....	10
10.3 Experimental apparatus (mass spectrometry).....	11
11 Test report.....	11
Bibliography.....	12