

# ISO/ASTM 52925:2022-04 (E)

## Additive manufacturing of polymers - Feedstock materials - Qualification of materials for laser-based powder bed fusion of parts

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols and abbreviations .....</b>	<b>1</b>
<b>4.1</b>	<b>Symbols .....</b>	<b>1</b>
<b>4.2</b>	<b>Abbreviations .....</b>	<b>2</b>
<b>5</b>	<b>Sampling .....</b>	<b>2</b>
<b>5.1</b>	<b>General .....</b>	<b>2</b>
<b>5.2</b>	<b>Characterisation of virgin powder and powder blends .....</b>	<b>2</b>
<b>5.3</b>	<b>Characterisation of used powder .....</b>	<b>2</b>
<b>6</b>	<b>Factory test report .....</b>	<b>3</b>
<b>6.1</b>	<b>General .....</b>	<b>3</b>
<b>6.2</b>	<b>Particle size distribution .....</b>	<b>3</b>
<b>6.3</b>	<b>Residual monomer content/extract content .....</b>	<b>3</b>
<b>6.4</b>	<b>Supplementary data .....</b>	<b>3</b>
<b>7</b>	<b>Factors influencing processability .....</b>	<b>4</b>
<b>7.1</b>	<b>General .....</b>	<b>4</b>
<b>7.2</b>	<b>Spreadability of the powder .....</b>	<b>4</b>
<b>7.3</b>	<b>Relative humidity of the powder (surface moisture) .....</b>	<b>4</b>
<b>7.4</b>	<b>Particle size distribution .....</b>	<b>5</b>
<b>8</b>	<b>Factors affecting part quality .....</b>	<b>5</b>
<b>8.1</b>	<b>General .....</b>	<b>5</b>
<b>8.2</b>	<b>Melting behaviour, melt flow and MVR .....</b>	<b>6</b>
<b>8.2.1</b>	<b>General .....</b>	<b>6</b>
<b>8.2.2</b>	<b>Laboratory methods .....</b>	<b>6</b>
<b>8.2.3</b>	<b>Melt volume-flow rate (MVR) .....</b>	<b>6</b>
<b>8.3</b>	<b>Melting temperature and recrystallisation temperature .....</b>	<b>7</b>
<b>Annex A (informative) Hausner ratio, HR .....</b>		<b>9</b>
<b>Annex B (informative) Determination of the melt volume-flow rate (MVR) .....</b>		<b>12</b>
<b>Annex C (informative) Round robin MVR test .....</b>		<b>15</b>
<b>Bibliography .....</b>		<b>18</b>