

# DIN EN 14574:2015-06 (E)

## Geosynthetics - Determination of the pyramid puncture resistance of supported geosynthetics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Principle .....</b>	<b>4</b>
<b>5</b>	<b>Apparatus .....</b>	<b>4</b>
<b>5.1</b>	<b>Test configuration .....</b>	<b>4</b>
<b>5.2</b>	<b>Underlying aluminium medium .....</b>	<b>5</b>
<b>5.3</b>	<b>Loading piston .....</b>	<b>5</b>
<b>5.4</b>	<b>Electrical equipment for the determination of the push-through load .....</b>	<b>6</b>
<b>6</b>	<b>Specimens .....</b>	<b>6</b>
<b>6.1</b>	<b>Sampling .....</b>	<b>6</b>
<b>6.2</b>	<b>Number and dimension of specimens .....</b>	<b>6</b>
<b>7</b>	<b>Conditioning .....</b>	<b>6</b>
<b>8</b>	<b>Procedure .....</b>	<b>7</b>
<b>9</b>	<b>Calculation and expression of test results .....</b>	<b>7</b>
<b>10</b>	<b>Test report .....</b>	<b>7</b>