

# DIN EN 13493:2018-07 (E)

## Geosynthetic barriers - Characteristics required for use in the construction of solid waste storage and disposal sites

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms, definitions and abbreviations .....</b>	<b>9</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>9</b>
<b>3.2</b>	<b>Abbreviations .....</b>	<b>11</b>
<b>4</b>	<b>Characteristics and corresponding methods of test .....</b>	<b>11</b>
<b>4.1</b>	<b>General .....</b>	<b>11</b>
<b>4.2</b>	<b>Types of application .....</b>	<b>12</b>
<b>4.2.1</b>	<b>General .....</b>	<b>12</b>
<b>4.2.2</b>	<b>Application 1: "Composite lining system" .....</b>	<b>12</b>
<b>4.2.3</b>	<b>Application 2: "Single lined system" .....</b>	<b>13</b>
<b>4.3</b>	<b>Relevant characteristics .....</b>	<b>13</b>
<b>4.4</b>	<b>Characteristics relevant to specific conditions of use .....</b>	<b>20</b>
<b>4.4.1</b>	<b>General .....</b>	<b>20</b>
<b>4.4.2</b>	<b>Gas permeability .....</b>	<b>20</b>
<b>4.4.3</b>	<b>Burst strength and elongation .....</b>	<b>20</b>
<b>4.4.4</b>	<b>Tear strength .....</b>	<b>20</b>
<b>4.4.5</b>	<b>Friction characteristics (direct shear and inclined plane tests) .....</b>	<b>20</b>
<b>4.4.6</b>	<b>Low temperature behaviour .....</b>	<b>20</b>
<b>4.4.7</b>	<b>Weathering .....</b>	<b>21</b>
<b>4.4.8</b>	<b>Resistance to wetting and drying .....</b>	<b>21</b>
<b>4.4.9</b>	<b>Freeze-thaw cycle resistance .....</b>	<b>21</b>
<b>4.4.10</b>	<b>Resistance to root penetration .....</b>	<b>21</b>
<b>4.5</b>	<b>Release of dangerous substances .....</b>	<b>21</b>
<b>5</b>	<b>Assessment and verification of constancy of performance (AVCP) .....</b>	<b>21</b>
<b>5.1</b>	<b>General .....</b>	<b>21</b>
<b>5.2</b>	<b>Type testing .....</b>	<b>22</b>
<b>5.2.1</b>	<b>General .....</b>	<b>22</b>
<b>5.2.2</b>	<b>Test samples, testing and compliance criteria .....</b>	<b>22</b>
<b>5.2.3</b>	<b>Test reports .....</b>	<b>23</b>
<b>5.2.4</b>	<b>Shared other party results .....</b>	<b>23</b>
<b>5.2.5</b>	<b>Cascading determination of the product type results .....</b>	<b>24</b>
<b>5.3</b>	<b>Factory production control (FPC) .....</b>	<b>25</b>
<b>5.3.1</b>	<b>General .....</b>	<b>25</b>
<b>5.3.2</b>	<b>Requirements .....</b>	<b>25</b>
<b>5.3.3</b>	<b>Product specific requirements .....</b>	<b>31</b>
<b>5.3.4</b>	<b>Initial inspection of factory and of FPC .....</b>	<b>32</b>
<b>5.3.5</b>	<b>Continuous surveillance of FPC .....</b>	<b>32</b>
<b>5.3.6</b>	<b>Procedure for modifications .....</b>	<b>32</b>
<b>5.3.7</b>	<b>One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity .....</b>	<b>32</b>
<b>Annex A (normative) Durability of geosynthetic barriers .....</b>		<b>34</b>

<b>A.1</b>	<b>General .....</b>	<b>34</b>
<b>A.2</b>	<b>Weathering .....</b>	<b>35</b>
<b>A.3</b>	<b>Products used with a service life up to 5 years .....</b>	<b>37</b>
<b>A.4</b>	<b>Other applications and service life of 25 and 50 years .....</b>	<b>37</b>
<b>A.5</b>	<b>Durability tests on GBR-P .....</b>	<b>43</b>
<b>A.6</b>	<b>Evaluation tests on GBR-P and GBR-C .....</b>	<b>49</b>
<b>A.7</b>	<b>Durability tests on GBR-B .....</b>	<b>50</b>
<b>A.8</b>	<b>Evaluation tests on GBR-B .....</b>	<b>54</b>
<b>Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No. 305/2011</b>		<b>56</b>
<b>Bibliography .....</b>		<b>60</b>