DIN EN 13492:2018-07 (E)

Geosynthetic barriers - Characteristics required for use in the construction of liquid waste disp osal sites, transfer stations or secondary containment

Contents

Page

European foreword 5

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms, definitions and abbreviations 10
3.1 Terms and definitions 10
3.2 Abbreviations 12

4 Characteristics and corresponding methods of test 13
4.1 General 13
4.2 Types of applications 13
4.2.1 General 13
4.2.2 Application 1: "Base and side barrier" 13
4.2.3 Application 2: "Cover barrier" 13
4.2.4 Application 3: "secondary containment of liquid waste" 14
4.3 Relevant characteristics 14
4.4 Characteristics relevant to specific conditions of use 21
4.4.1 General 21
4.4.2 Gas permeability 21
4.4.3 Burst strength and elongation 21
4.4.4 Tear strength 21
4.4.5 Friction characteristics (direct shear and inclined plane tests) 21
4.4.6 Low temperature behaviour 21
4.4.7 Weathering 22
4.4.8 Resistance to wetting and drying 22
4.4.9 Freeze-thaw cycle resistance 22
4.4.10 Resistance to root penetration 22
4.5 Release of dangerous substances 22

5 Assessment and verification of constancy of performance (AVCP) 22
5.1 General 22
5.2 Type testing 23
5.2.1 General 23
5.2.2 Test samples, testing and compliance criteria 24
5.2.3 Test reports 24
5.2.4 Shared other party results 24
5.2.5 Cascading determination of the product type results 25
5.3 Factory production control (FPC) 26
5.3.1 General 26
5.3.2 Requirements 26
5.3.3 Product specific requirements 32
5.3.4 Initial inspection of factory and of FPC 32
5.3.5 Continuous surveillance of FPC 33
5.3.6 Procedure for modifications 33
5.3.7 One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity 33

Annex A (normative) Durability of geosynthetic barriers 35

A.1 General 35
A.1.1 Service Life 35
A.1.2 Type testing of durability 35
A.1.3 Mechanisms of degradation 36
A.1.4 Use of rework material 36
A.1.5 Recycled materials 36
A.2 Weathering 36
A.2.1 General 36
A.2.2 Direct tests and accelerated tests 37
A.2.3 Period of exposure 37
A.3 Products used with a service life up to 5 years 38
A.4 Other applications and service life of 25 and 50 years 38
A.4.1 General 38
A.4.2 Tests for PE type of GBR-P 39
A.4.3 Tests for FPO-type of GBR-P 40
A.4.4 Tests for EPDM type of GBR-P 41
A.4.5 Tests for GBR-P made of PVC-P 41
A.4.6 Tests for clay geosynthetic barriers (GBR-C) 42
A.5 Durability tests on GBR-P 44
A.5.1 Introduction 44
A.5.2 Microbiological resistance 44
A.5.3 Resistance to environmental stress cracking 45
A.5.4 Resistance to leaching 46
A.5.5 Resistance to oxidation/thermal ageing 48
A.6 Evaluation tests on GBR-P and GBR-C 50
A.6.1 General 50
A.6.2 Evaluation by comparison of tensile properties 50
A.6.3 Evaluation by comparison of oxidative induction time (OIT) values 51
A.6.4 Evaluation by change in mass 51
A.6.5 Evaluation by change in water permeability 51
A.7 Durability tests on GBR-B 51
A.7.1 Introduction 51
A.7.2 Microbiological resistance 52
A.7.3 Resistance to environmental stress cracking 52
A.7.4 Resistance to leaching 53
A.7.5 Resistance to oxidation/thermal ageing 54
A.7.6 Weathering resistance 54
A.8 Evaluation tests on GBR-B 55
A.8.1 General 55
A.8.2 Evaluation by comparison of tensile properties 55
A.8.3 Evaluation by change in mass 55
A.8.4 Evaluation of water permeability 55
A.8.5 Evaluation of flow resistance at elevated temperature 56
A.8.6 Evaluation of flexibility at low temperature 56
A.8.7 Evaluation of ring and ball softening point temperature 56

Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No. 305/2011 57

ZA.1 Scope and relevant characteristics 57

ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP) 59

ZA.3 Assignment of AVCP tasks 59

Bibliography 61