ISO/TR 18228-3:2021 (E)

Design using geosynthetics — Part 3: Filtration

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions
3.2 Symbols
3.3 Abbreviated terms

4 Concepts and fundamental principles

4.1 General
4.2 The filtration function of geotextiles
4.3 Filter selection fundamentals

5 Typical applications

5.1 General considerations
5.2 Soil filtration
5.3 Slurry filtration

6 Materials

7 Functional properties relevant to design

7.1 Characteristic opening size
7.2 Velocity index and permittivity (permeability)
7.3 Resistance to water penetration
7.4 Number of constrictions
7.5 Percent open area

8 Principles of design

8.1 General considerations
8.2 Designing geotextiles for soil filtration
8.2.1 General
8.2.2 Retention criteria of the soil skeleton
8.2.3 Non-retention criteria of fines in suspension
8.2.4 Permeability criteria
8.3 Designing geotextiles for slurry and suspended solids filtration

9 Testing the soil/geotextile filtration compatibility

9.1 General
9.2 Soil/geotextile compatibility
9.2.1 Gradient ratio
9.2.2 Hydraulic conductivity ratio
9.2.3 Retention performance of geotextiles exposed to turbulent flow conditions
9.3 Evaluation of slurry/geotextile behaviour
9.4 Biological or chemical clogging potential
9.5 Impact of abrasion on the filtration properties of geotextiles
9.5.1 Abrasion resistance – Index property
9.5.2 Abrasion resistance – Rotary drum method

10 Examples of material specifications and design guidance

Page count: 20