

ISO/TR 18228-9:2022-04 (E)

Design using geosynthetics - Part 9: Barriers

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Pictograms	2
4.1	Product and function	2
4.2	Applications	2
4.2.1	Containment application, non-landfill (CA)	2
4.2.2	Chemical containment, non-landfill (CC)	2
4.2.3	Construction waterproofing (CW)	3
4.2.4	Landfill base lining (LBL)	3
4.2.5	Landfills caps (LC)	3
4.2.6	Secondary containment (SC)	4
4.2.7	Transport infrastructure applications (TIA)	4
4.2.8	Tunnels (Tu)	5
4.2.9	Water retaining structure (WRS-e), e.g. balancing ponds, dams, dykes and canals (usually empty)	5
4.2.10	Water retaining structure (WRS-f), e.g. reservoirs, canals (usually full)	5
5	Design Criteria	6
6	Materials	7
6.1	General	7
6.2	HDPE	7
6.3	LLDPE	7
6.4	fPP	7
6.5	PVC	7
6.6	EPDM	7
6.7	Bitumen	7
6.8	EIA (ethylene interpolymer alloy)	7
6.9	Bentonite	7
6.10	Sodium bentonite	8
6.11	Calcium bentonite	8
7	Properties relevant to design	8
7.1	General	8
7.2	Chemical resistance	9
7.3	Physical properties	9
7.4	Durability/weathering	10
7.4.1	General	10
7.4.2	Mechanisms of degradation of the GBR	10
7.4.3	Mechanisms of degradation of the joints	10
8	Principles of design	11
8.1	General	11
8.2	Subgrade preparation	11

8.3	Slope stability	11
8.4	Climate conditions	12
8.5	Temperature effects (thermal expansion and stiffness)	12
8.6	Protection and testing	12
8.6.1	Puncture protection	12
8.6.2	Installation issues, excluding jointing	12
8.6.3	QC on site	13
8.6.4	Hydraulic uplift	14
ISO/TR 18228-9:2022(E) 9 Example design chart		14
Bibliography		16