

ISO/TS 18198:2023-03 (E)

Determination of long-term flow of geosynthetic drains

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Test equipment and procedures for determination of short-term in- plane water flow	1
4.1	Measurement of maximum hydraulic transmissivity and flow rate	1
4.2	Test equipment	2
4.2.1	Unidirectional flow	2
4.2.2	Index and performance tests	5
4.3	Normal compressive loading and seating time	5
4.4	Number of test specimens per sample per test	6
4.5	Hydraulic gradient	7
5	Determination of long-term flow performance	7
5.1	General	7
5.2	Reduction factors (RF)	8
5.3	Reduction factor for intrusion (RF,in and RF,GI)	9
5.4	Reduction factor for creep (RF,cr)	10
5.4.1	General	10
5.4.2	Time-temperature superposition methods	11
5.5	Reduction factors for chemical clogging (RF,CC) and biological clogging (RF,BC)	12
5.6	Additional considerations	13
5.6.1	Design life	13
5.6.2	Design temperature	13
5.6.3	Installation damage	14
5.6.4	Durability of the polymers	14
6	Alternative procedures to determine Qa	14
6.1	General	14
6.2	Long-term reduction of water flow capacity due to compressive creep by the BAM (Germany) method	14
6.3	Thickness-dependent short-term flow testing using SIM	17
6.4	Time dependent loading followed by flow capacity measurements	19
Bibliography		20