ISO/TS 18198:2023-03 (E)

Determination of long-term flow of geosynthetic drains

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Test equipment and procedures for determination of short-term in- plane water flow 1
4.1 Measurement of maximum hydraulic transmissivity and flow rate 1
4.2 Test equipment 2
4.2.1 Unidirectional flow 2
4.2.2 Index and performance tests 5
4.3 Normal compressive loading and seating time 5
4.4 Number of test specimens per sample per test 6
4.5 Hydraulic gradient 7

5 Determination of long-term flow performance 7
5.1 General 7
5.2 Reduction factors (RF) 8
5.3 Reduction factor for intrusion (RF,in and RF,GI) 9
5.4 Reduction factor for creep (RF,cr) 10
5.4.1 General 10
5.4.2 Time-temperature superposition methods 11
5.5 Reduction factors for chemical clogging (RF,CC) and biological clogging (RF,BC) 12
5.6 Additional considerations 13
5.6.1 Design life 13
5.6.2 Design temperature 13
5.6.3 Installation damage 14
5.6.4 Durability of the polymers 14

6 Alternative procedures to determine Qa 14
6.1 General 14
6.2 Long-term reduction of water flow capacity due to compressive creep by the BAM (Germany) method 14
6.3 Thickness-dependent short-term flow testing using SIM 17
6.4 Time dependent loading followed by flow capacity measurements 19

Bibliography 20