

# DIN EN ISO 9073-18:2024-11 (E)

Nonwovens - Test methods - Part 18: Determination of tensile strength and elongation at break using the grab tensile test (ISO 9073-18:2023, Corrected version 2024-05)

---

## Contents

Page

European foreword.....	3
Foreword.....	4
<b>1 Scope.....</b>	<b>6</b>
<b>2 Normative references.....</b>	<b>6</b>
<b>3 Terms and definitions.....</b>	<b>6</b>
<b>4 Principle.....</b>	<b>8</b>
<b>5 Reagents and materials.....</b>	<b>8</b>
<b>6 Apparatus.....</b>	<b>8</b>
<b>7 Sampling.....</b>	<b>9</b>
7.1 Lot sampling.....	9
7.2 Laboratory sample.....	10
7.3 Test specimens.....	10
<b>8 Conditioning.....</b>	<b>10</b>
<b>9 Preparation of test specimens.....</b>	<b>11</b>
9.1 General.....	11
9.2 Dimensions.....	11
9.3 Marking on the test specimen.....	11
9.4 Wet test specimens.....	11
<b>10 Preparation, calibration and verification of apparatus.....</b>	<b>11</b>
10.1 Tensile testing machine.....	11
10.2 Clamping system.....	12
10.3 Verification of the total operating system of the apparatus.....	12
<b>11 Procedure.....</b>	<b>12</b>
11.1 Gauge length.....	12
11.2 Rate of extension.....	13
11.3 Mounting of test specimens.....	13
11.4 Operation.....	13
11.4.1 General.....	13
11.4.2 Slippage.....	13
11.4.3 Jaw breaks.....	13
<b>12 Calculation.....</b>	<b>14</b>
12.1 Breaking force.....	14
12.2 Apparent elongation.....	14
<b>13 Expression of results.....</b>	<b>14</b>
<b>14 Precision and bias.....</b>	<b>14</b>
<b>15 Test report.....</b>	<b>14</b>
<b>Annex A (informative) Possible causes of low precision when grab strength testing.....</b>	<b>16</b>
<b>Bibliography.....</b>	<b>17</b>