

# DIN EN 13492:2006-10 (E)

## Geosynthetic barriers - Characteristics required for use in the construction of liquid waste disposal sites, transfer stations or secondary containment

---

Contents	Page
<b>Introduction .....</b>	<b>5</b>
<b>1 Scope .....</b>	<b>6</b>
<b>2 Normative references .....</b>	<b>6</b>
<b>3 Definitions and abbreviations .....</b>	<b>8</b>
<b>3.1 Definitions .....</b>	<b>8</b>
<b>3.2 Abbreviations .....</b>	<b>9</b>
<b>4 Required characteristics and corresponding methods of test .....</b>	<b>9</b>
<b>4.1 General .....</b>	<b>9</b>
<b>4.2 Relevant characteristics .....</b>	<b>9</b>
<b>4.3 Characteristics relevant to specific conditions of use .....</b>	<b>12</b>
<b>4.3.1 Tear strength .....</b>	<b>12</b>
<b>4.3.2 Bursting strength .....</b>	<b>12</b>
<b>4.3.3 Friction characteristics (direct shear and inclined plane tests) .....</b>	<b>12</b>
<b>4.3.4 Low temperature behaviour .....</b>	<b>12</b>
<b>4.3.5 Weathering .....</b>	<b>12</b>
<b>4.3.6 Resistance to wetting and drying .....</b>	<b>12</b>
<b>4.3.7 Freeze-thaw cycle resistance .....</b>	<b>13</b>
<b>4.3.8 Resistance to root penetration .....</b>	<b>13</b>
<b>5 Evaluation of conformity .....</b>	<b>13</b>
<b>5.1 Presentation of characteristics .....</b>	<b>13</b>
<b>5.2 Verification of values .....</b>	<b>13</b>
<b>5.3 Initial type tests .....</b>	<b>13</b>
<b>5.4 Factory production control .....</b>	<b>14</b>
<b>5.5 Inspection .....</b>	<b>14</b>
<b>6 Marking .....</b>	<b>14</b>
<b>Annex A (normative) Scheme of factory production control .....</b>	<b>15</b>
<b>A.1 Product design .....</b>	<b>15</b>
<b>A.2 Production .....</b>	<b>15</b>
<b>A.3 Finished products .....</b>	<b>15</b>
<b>A.4 Equipment .....</b>	<b>15</b>
<b>A.5 Provisions applicable to A.1, A.2 and A.3 (to be used where appropriate) .....</b>	<b>16</b>
<b>Annex B (normative) Durability of geosynthetic barriers .....</b>	<b>17</b>
<b>B.1 Introduction .....</b>	<b>17</b>
<b>B.2 Evaluation of durability tests and acceptance criteria .....</b>	<b>18</b>
<b>B.3 Weathering .....</b>	<b>18</b>
<b>B.3.1 Direct tests .....</b>	<b>18</b>
<b>B.3.2 Period of exposure .....</b>	<b>19</b>
<b>B.4 Resistance to micro-organisms .....</b>	<b>20</b>
<b>B.5 Resistance to root penetration .....</b>	<b>20</b>
<b>B.6 Resistance to environmental stress cracking .....</b>	<b>20</b>
<b>B.7 Resistance to leaching .....</b>	<b>21</b>

<b>B.8</b>	<b>Resistance to oxidation .....</b>	<b>21</b>
<b>B.9</b>	<b>Chemical resistance for landfill applications .....</b>	<b>21</b>
<b>B.9.1</b>	<b>All applications .....</b>	<b>21</b>
<b>B.10</b>	<b>Geosynthetic clay barriers .....</b>	<b>22</b>
<b>Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive .....</b>		<b>23</b>
<b>ZA.1 Scope and relevant characteristics .....</b>		<b>23</b>
<b>ZA.2 System of attestation of conformity for Geomembranes used in the construction of liquid waste disposal sites, transfer stations and secondary containment .....</b>		<b>24</b>
<b>ZA.3 CE marking and labelling .....</b>		<b>26</b>
<b>Bibliography .....</b>		<b>30</b>
<b>Figures Figure ZA.1 -- Example of CE marking on the packaging of a Geosynthetic Barrier .....</b>		<b>27</b>
<b>Figure ZA.2 -- Example of accompanying documents .....</b>		<b>28</b>
<b>Tables Table 1 -- Geosynthetic Barriers used in the construction of liquid waste disposal sites, transfer stations and secondary containment - Functions, function-related characteristics and test methods to be used .....</b>		<b>10</b>
<b>Table 2 -- Characteristics required for initial type testing and evaluation of conformity .....</b>		<b>14</b>
<b>Table B.1 -- Required weathering radiant exposure (&gt; 75 % retained tensile properties ) .....</b>		<b>20</b>
<b>Table ZA.1 -- Scope and relevant clauses .....</b>		<b>24</b>
<b>Table ZA.2 -- System of attestation of conformity .....</b>		<b>25</b>
<b>Table ZA.3 -- Assignation of evaluation of conformity tasks (for geosynthetic barriers under system 2+) .....</b>		<b>25</b>