

DIN EN 13492:2006-10 (E)

Geosynthetic barriers - Characteristics required for use in the construction of liquid waste disposal sites, transfer stations or secondary containment

Contents		Page
Introduction		5
1	Scope	6
2	Normative references	6
3	Definitions and abbreviations	8
3.1	Definitions	8
3.2	Abbreviations	9
4	Required characteristics and corresponding methods of test	9
4.1	General	9
4.2	Relevant characteristics	9
4.3	Characteristics relevant to specific conditions of use	12
4.3.1	Tear strength	12
4.3.2	Bursting strength	12
4.3.3	Friction characteristics (direct shear and inclined plane tests)	12
4.3.4	Low temperature behaviour	12
4.3.5	Weathering	12
4.3.6	Resistance to wetting and drying	12
4.3.7	Freeze-thaw cycle resistance	13
4.3.8	Resistance to root penetration	13
5	Evaluation of conformity	13
5.1	Presentation of characteristics	13
5.2	Verification of values	13
5.3	Initial type tests	13
5.4	Factory production control	14
5.5	Inspection	14
6	Marking	14
Annex A (normative) Scheme of factory production control		15
A.1	Product design	15
A.2	Production	15
A.3	Finished products	15
A.4	Equipment	15
A.5	Provisions applicable to A.1, A.2 and A.3 (to be used where appropriate)	16
Annex B (normative) Durability of geosynthetic barriers		17
B.1	Introduction	17
B.2	Evaluation of durability tests and acceptance criteria	18
B.3	Weathering	18
B.3.1	Direct tests	18
B.3.2	Period of exposure	19
B.4	Resistance to micro-organisms	20
B.5	Resistance to root penetration	20
B.6	Resistance to environmental stress cracking	20
B.7	Resistance to leaching	21

B.8	Resistance to oxidation	21
B.9	Chemical resistance for landfill applications	21
B.9.1	All applications	21
B.10	Geosynthetic clay barriers	22
Annex ZA (informative)	Clauses of this European Standard addressing the provisions of the EU Construction Products Directive	23
ZA.1	Scope and relevant characteristics	23
ZA.2	System of attestation of conformity for Geomembranes used in the construction of liquid waste disposal sites, transfer stations and secondary containment	24
ZA.3	CE marking and labelling	26
	Bibliography	30
Figures	Figure ZA.1 -- Example of CE marking on the packaging of a Geosynthetic Barrier	27
	Figure ZA.2 -- Example of accompanying documents	28
Tables	Table 1 -- Geosynthetic Barriers used in the construction of liquid waste disposal sites, transfer stations and secondary containment - Functions, function-related characteristics and test methods to be used	10
	Table 2 -- Characteristics required for initial type testing and evaluation of conformity	14
	Table B.1 -- Required weathering radiant exposure (> 75 % retained tensile properties)	20
	Table ZA.1 -- Scope and relevant clauses	24
	Table ZA.2 -- System of attestation of conformity	25
	Table ZA.3 -- Assignment of evaluation of conformity tasks (for geosynthetic barriers under system 2+)	25