

# ISO/TR 10064-2:1996-03 (E)

## Cylindrical gears - Code of inspection practice - Part 2: Inspection related to radial composite deviations, runout, tooth thickness and backlash

---

Contents	Page
FOREWORD .....	IV
1 Scope .....	1
2 References .....	1
3 Symbols, corresponding terms and definitions .....	2
3.1 Lower case symbols .....	2
3.2 Upper case symbols .....	2
3.3 Greek symbols .....	2
3.4 Subscript symbols .....	2
3.5 Definitions .....	3
4 Measurement of radial composite deviations .....	6
4.1 Checking principle .....	6
4.2 The Utility of radial composite deviation data .....	7
5 Measurement of runout, determining eccentricity .....	8
5.1 Measuring principle .....	8
5.2 Anvil size for measuring runout .....	9
5.3 Measuring runout .....	9
5.4 Evaluation of measurement 1 .....	1
5.5 Value of runout measurement .....	11
5.6 The relation between runout and pitch deviations .....	11
6 Measurement of tooth thickness, tooth span and dimension over balls or cylinders .....	14
6.1 Tooth thickness measurement .....	14
6.2 Span measurement .....	15
6.3 Control of tooth thickness by determining the dimension over balls or cylinders .....	17
6.4 Tooth thickness measurement with radial composite measurement .....	19
6.5 Calculations for radial composite action test measurement .....	19
7 Gear limits and fits .....	21
7.1 Introduction .....	21
7.2 Tooth thickness tolerances .....	22
Annex A Backlash and Tooth Thickness Tolerance .....	23
A.1 Purpose .....	23
A.2 Backlash .....	23
A.3 Maximum Tooth Thickness .....	23
A.4 Minimum Backlash .....	23
A.5 Specifications for Tooth Thickness Measurement .....	24
A.6 Maximum Backlash .....	24
Annex B Bibliography .....	26
TABLES	
Table 1 - Standard pin diameters in mm .....	17
Table A1 - Recommended values minimum backlash for coarse pitch gears .....	24

**FIGURES**

Figure 1 - Span and tooth thickness allowances ..... 4

Figure 2 - Tooth thickness, transverse plane ..... 5

Figure 3 - Relationship between circumferential  $j_{wt}$ , normal  $j_{bn}$ , and radial  $j_r$  backlash ..... 6

Figure 4 - Principle of measuring radial composite deviations ..... 7

Figure 5 - Radial composite deviation diagram ..... 7

Figure 6 - Interpretation of radial composite deviation ..... 8

Figure 7 - Principle of measuring runout ..... 9

Figure 8 - Anvil size for measuring runout..... 10

Figure 9 - Runout from coordinate measuring machine..... 10

Figure 10 - Runout diagram of a gear with 16 teeth 1 ..... 1

Figure 11 - Runout and pitch deviations of an eccentric gear ..... 12

Figure 12 - Gear with zero runout, but with considerable pitch and cumulative pitch deviations (all space widths are equal) ..... 12

Figure 13 - Gear with pitch and cumulative pitch deviations and zero runout ..... 13

Figure 14 - Actual gear with little runout and substantial cumulative pitch deviation ..... 13

Figure 15 - Runout measurement with a rider when all space widths are equal and pitch deviations are present ..... 14

Figure 16 - Addendum and chordal tooth thickness ..... 14

Figure 17 - Chordal tooth thickness measurement by gear tooth caliper ..... 15

Figure 18 - Span measurement of helical gears ..... 15

Figure 19 - Limits of span measurement in base tangent plane..... 16

Figure 20 - Dimension over (between) balls or cylinders for spur gear teeth ..... 17

Figure 21 - Ball size ..... 18

Figure 22 - Radical composite action test measurement of tooth thickness ..... 20

Figure 23 - Fit of gear teeth..... 21

Figure A1 - Feeler gauge backlash measurement (normal plane)..... 23