

# ISO/TR 10064-2:1996-03 (E)

## Cylindrical gears - Code of inspection practice - Part 2: Inspection related to radial composite deviations, runout, tooth thickness and backlash

---

<b>Contents</b>	<b>Page</b>
<b>FOREWORD</b> .....	<b>IV</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 References</b> .....	<b>1</b>
<b>3 Symbols, corresponding terms and definitions</b> .....	<b>2</b>
<b>3.1 Lower case symbols</b> .....	<b>2</b>
<b>3.2 Upper case symbols</b> .....	<b>2</b>
<b>3.3 Greek symbols</b> .....	<b>2</b>
<b>3.4 Subscript symbols</b> .....	<b>2</b>
<b>3.5 Definitions</b> .....	<b>3</b>
<b>4 Measurement of radial composite deviations</b> .....	<b>6</b>
<b>4.1 Checking principle</b> .....	<b>6</b>
<b>4.2 The Utility of radial composite deviation data</b> .....	<b>7</b>
<b>5 Measurement of runout, determining eccentricity</b> .....	<b>8</b>
<b>5.1 Measuring principle</b> .....	<b>8</b>
<b>5.2 Anvil size for measuring runout</b> .....	<b>9</b>
<b>5.3 Measuring runout</b> .....	<b>9</b>
<b>5.4 Evaluation of measurement 1</b> .....	<b>1</b>
<b>5.5 Value of runout measurement</b> .....	<b>11</b>
<b>5.6 The relation between runout and pitch deviations</b> .....	<b>11</b>
<b>6 Measurement of tooth thickness, tooth span and dimension over balls or cylinders</b> .....	<b>14</b>
<b>6.1 Tooth thickness measurement</b> .....	<b>14</b>
<b>6.2 Span measurement</b> .....	<b>15</b>
<b>6.3 Control of tooth thickness by determining the dimension over balls or cylinders</b> .....	<b>17</b>
<b>6.4 Tooth thickness measurement with radial composite measurement</b> .....	<b>19</b>
<b>6.5 Calculations for radial composite action test measurement</b> .....	<b>19</b>
<b>7 Gear limits and fits</b> .....	<b>21</b>
<b>7.1 Introduction</b> .....	<b>21</b>
<b>7.2 Tooth thickness tolerances</b> .....	<b>22</b>
<b>Annex A Backlash and Tooth Thickness Tolerance</b> .....	<b>23</b>
<b>A.1 Purpose</b> .....	<b>23</b>
<b>A.2 Backlash</b> .....	<b>23</b>
<b>A.3 Maximum Tooth Thickness</b> .....	<b>23</b>
<b>A.4 Minimum Backlash</b> .....	<b>23</b>
<b>A.5 Specifications for Tooth Thickness Measurement</b> .....	<b>24</b>
<b>A.6 Maximum Backlash</b> .....	<b>24</b>
<b>Annex B Bibliography</b> .....	<b>26</b>
<b>TABLES</b>	
<b>Table 1 - Standard pin diameters in mm</b> .....	<b>17</b>
<b>Table A1 - Recommended values minimum backlash for coarse pitch gears</b> .....	<b>24</b>

**FIGURES**

Figure 1 - Span and tooth thickness allowances ..... 4

Figure 2 - Tooth thickness, transverse plane ..... 5

Figure 3 - Relationship between circumferential  $j_{wt}$ , normal  $j_{bn}$ , and radial  $j_r$  backlash ..... 6

Figure 4 - Principle of measuring radial composite deviations ..... 7

Figure 5 - Radial composite deviation diagram ..... 7

Figure 6 - Interpretation of radial composite deviation ..... 8

Figure 7 - Principle of measuring runout ..... 9

Figure 8 - Anvil size for measuring runout..... 10

Figure 9 - Runout from coordinate measuring machine..... 10

Figure 10 - Runout diagram of a gear with 16 teeth 1 ..... 1

Figure 11 - Runout and pitch deviations of an eccentric gear ..... 12

Figure 12 - Gear with zero runout, but with considerable pitch and cumulative pitch deviations (all space widths are equal) ..... 12

Figure 13 - Gear with pitch and cumulative pitch deviations and zero runout ..... 13

Figure 14 - Actual gear with little runout and substantial cumulative pitch deviation ..... 13

Figure 15 - Runout measurement with a rider when all space widths are equal and pitch deviations are present ..... 14

Figure 16 - Addendum and chordal tooth thickness ..... 14

Figure 17 - Chordal tooth thickness measurement by gear tooth caliper ..... 15

Figure 18 - Span measurement of helical gears ..... 15

Figure 19 - Limits of span measurement in base tangent plane..... 16

Figure 20 - Dimension over (between) balls or cylinders for spur gear teeth ..... 17

Figure 21 - Ball size ..... 18

Figure 22 - Radical composite action test measurement of tooth thickness ..... 20

Figure 23 - Fit of gear teeth..... 21

Figure A1 - Feeler gauge backlash measurement (normal plane)..... 23