ISO/TR 10064-2:1996-03 (E)

Cylindrical gears - Code of inspection practice - Part 2: Inspection related to radial composite deviations, runout, tooth thickness and backlash

Contents

Page

FOREWORD IV

1 Scope 1

2 References 1

3 Symbols, corresponding terms and definitions 2
3.1 Lower case symbols 2
3.2 Upper case symbols 2
3.3 Greek symbols 2
3.4 Subscript symbols 2
3.5 Definitions 3

4 Measurement of radial composite deviations 6
4.1 Checking principle 6
4.2 The Utility of radial composite deviation data 7

5 Measurement of runout, determining eccentricity 8
5.1 Measuring principle 8
5.2 Anvil size for measuring runout 9
5.3 Measuring runout 9
5.4 Evaluation of measurement 1 1
5.5 Value of runout measurement 11
5.6 The relation between runout and pitch deviations 11

6 Measurement of tooth thickness, tooth span and dimension over balls or cylinders 14
6.1 Tooth thickness measurement 14
6.2 Span measurement 15
6.3 Control of tooth thickness by determining the dimension over balls or cylinders 17
6.4 Tooth thickness measurement with radial composite measurement 19
6.5 Calculations for radial composite action test measurement 19

7 Gear limits and fits 21
7.1 Introduction 21
7.2 Tooth thickness tolerances 22

Annex A Backlash and Tooth Thickness Tolerance 23
A.1 Purpose 23
A.2 Backlash 23
A.3 Maximum Tooth Thickness 23
A.4 Minimum Backlash 23
A.5 Specifications for Tooth Thickness Measurement 24
A.6 Maximum Backlash 24

Annex B Bibliography 26

TABLES

Table 1 - Standard pin diameters in mm 17

Table A1 - Recommended values minimum backlash for coarse pitch gears 24

FIGURES

Figure 1 - Span and tooth thickness allowances 4

Figure 2 - Tooth thickness, transverse plane 5

Figure 3 - Relationship between circumferential j_{wt}, normal j_{bn}, and radial j_r backlash 6

Figure 4 - Principle of measuring radial composite deviations 7

Figure 5 - Radial composite deviation diagram 7

Figure 6 - Interpretation of radial composite deviation 8

Figure 7 - Principle of measuring runout 9

Figure 8 - Anvil size for measuring runout 10

Figure 9 - Runout from coordinate measuring machine 10

Figure 10 - Runout diagram of a gear with 16 teeth 1 1

Figure 11 - Runout and pitch deviations of an eccentric gear 12

Figure 12 - Gear with zero runout, but with considerable pitch and cumulative pitch deviations (all space widths are equal) 12

Figure 13 - Gear with pitch and cumulative pitch deviations and zero runout 13

Figure 14 - Actual gear with little runout and substantial cumulative pitch deviation 13

Figure 15 - Runout measurement with a rider when all space widths are equal and pitch deviations are present 14

Figure 16 - Addendum and chordal tooth thickness 14

Figure 17 - Chordal tooth thickness measurement by gear tooth caliper 15

Figure 18 - Span measurement of helical gears 15

Figure 19 - Limits of span measurement in base tangent plane 16

Figure 20 - Dimension over (between) balls or cylinders for spur gear teeth 17

Figure 21 - Ball size 18

Figure 22 - Radical composite action test measurement of tooth thickness 20

Figure 23 - Fit of gear teeth 21

Figure A1 - Feeler gauge backlash measurement (normal plane) 23