DIN SPEC 16593-1:2018-04 (E)

RM-SA - Reference Model for Industrie 4.0 Service Architectures - Part 1: Basic Concepts of an Interaction-based Architecture; Text in English

Inhalt

Seite

Foreword 4

Introduction 6

1 Scope 8
1.1 RAMI4.0 dimensions 8
1.2 SOA reference models 9
1.3 Value chains 10

2 Normative references 10

3 Terms and definitions 11

4 Symbols and abbreviated terms 14

5 Architectural foundation 15

6 Reference Models for Service-oriented Architecture 16
6.1 Overview 16
6.2 ISO/IEC 10746-1:1998 reference model for open distributed processing 16
6.3 OASIS Reference Model for Service-oriented Architectures 17

7 Conceptual interaction model 19
7.1 General 19
7.2 Basic considerations 20
7.2.1 Object worlds 20
7.2.2 Systems and components 20
7.2.3 Intra-component view: behavior, states, procedures and change events 22
7.2.4 Extra-component view: signal events, call events and interfaces 24
7.2.5 Inter-component view: primitives and notifications 25
7.2.6 Inter-component view: interactions, interaction patterns and interaction policies 25
7.3 Service 28
7.3.1 Definition 28
7.3.2 Service types 29
7.3.3 Infrastructure services 30
7.3.4 Interaction-based services 31

8 Characterization of interactions 36
8.1 Classification of interactions 36
8.1.1 General 36
8.1.2 Determinism 36
8.1.3 Synchronicity 36
8.1.4 State handling 36
8.2 Interaction patterns 37
8.2.1 General 37
8.2.2 Unicast 37
8.2.3 Multicast 38
8.2.4 Request-response 39
8.2.5 Multicast request-response 40
8.2.6 Use and observation 41
8.2.7 Publish-find-bind-execute 42
8.3 Characterization of interaction classes 43

9 Compliance 44
Annex A (informative) Terminological Service Discussion 45
Annex B (informative) Mapping examples to OPC UA 46
B.1 General 46
B.2 OPC UA read service 46
B.3 OPC UA PublishRequest 47
Bibliography 48

Figures

Figure 1 — RAMI4.0 dimensions and I4.0 component abstraction 8
Figure 2 — Reference models enable architecture specifications 9
Figure 3 — Influencing Factors of the RM-SA 15
Figure 4 — Concepts of OASIS SOA reference model 17
Figure 5 — IBA Conceptual interaction model 19
Figure 6 — RM-SA system model 20
Figure 7 — Component and its associated object worlds (derived from DIN SPEC 91345:2016-04, Figure 1) (left-hand side complete, right-hand side restricted for simplification reasons) 21
Figure 8 — Graphic representation of a UML state machine diagram (example) 23
Figure 9 — Projection of the functionality (in terms of procedures) and states of a component 24
Figure 10 — Exchange of primitives and notifications between components 25
Figure 11 — Interaction policies and domains 27
Figure 12 — Service types in an Industrie 4.0 System 29
Figure 13 — Mapping of interaction-based services to infrastructure services 30
Figure 14 — Infrastructure services according to ISO/IEC 7498-1:1994 OSI Model 31
Figure 15 — Spectrum of architectural styles of interaction-based services 32
Figure 16 — Functional services as remote operations 33
Figure 17 — Procedure-based interaction mapped to infrastructure services (note: illustration restricted to a procedure call) 34
Figure 18 — State machine-based interaction mapped to infrastructure services 35
Figure 19 — Interaction pattern “unicast” 37
Figure 20 — Interaction pattern “multicast” 38
Figure 21 — Interaction pattern “request-response” 39
Figure 22 — Interaction pattern “multicast request-response” 40
Figure 23 — Interaction pattern “use and observation” 41
Figure 24 — Interaction pattern “publish – find – bind – execute” 42
Figure B.1 — OPC UA Read Service 46
Figure B.2 — OPC UA PublishRequest 47