DIN SPEC 54789:2020-05 (E)

Fine Bubble Technology - Fine Bubble Induced Gas Flotation Devices - Installation and Operation; Text in English

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Symbols and abbreviations 8

5 Principle 9

6 Requirements 9
6.1 General 9
6.2 Installation 11
6.3 Required accessories 12
6.3.1 Level sensor (tank) (see Figure 1, 15) 12
6.3.2 Pressurized gas filter (see Figure 1, 14) 12
6.3.3 Pressurized gas pressure control valve (see Figure 1, 12) 12
6.3.4 Pressure sensor(s) (see Figure 1, 11) 12
6.3.5 Temperature sensor (see Figure 1, 8) 12
6.4 Optional accessories 12
6.4.1 Pressurized gas flowmeter (see Figure 1, 12) 12
6.4.2 Chemical flush (CF) pump 12
6.5 Process requirements 12
6.5.1 Bubble contact zone 12
6.5.2 Superficial wastewater flux 13
6.5.3 Wastewater inlet and outlet 13
6.5.4 Gas demand 13
6.5.5 Superficial gas flux 13

7 Operation 13
7.1 General 13
7.2 Initial start-up 13
7.3 Tune-up 14
7.4 Chemical cleaning 15
7.4.1 Cleaning solutions 15
7.4.2 Cleaning in place (CIP) 16
7.4.3 Chemical flush (CF) 16
7.5 Shut down 16

Annex A (informative) Method of measuring visible depth 18
A.1 General 18
A.2 Apparatus 18
A.3 Procedure 18
A.4 Expression of results 18

Annex B (informative) Commissioning procedure 20
B.1 General 20
B.2 Procedure 20
B.2.1 Dry commissioning 20

B.2.2 Wet commissioning 20
B.2.3 Process commissioning in manual and automatic mode 20
Bibliography 21

Figures

Figure 1 — Process flow diagram for an induced gas flotation device 11
Figure 2 — Cleaning method decision chart 17
Figure A.1 — Transparency testing disk 19

Tables

Table 1 — Allowed water conditions (inlet) 10
Table 2 — Possible cleaning solutions (examples) 15