

DIN SPEC 91437:2023-05 (E)

Liquid Organic Hydrogen Carrier (LOHC) based on toluene - Evaluation, testing and assurance of LOHC quality; Text in English

Contents

	Page
Foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Description of LOHC technology	6
5 Requirements for usage as LOHC	7
5.1 General	7
5.2 LOHC-0 material	8
5.2.1 Material properties	8
5.2.2 Further substances	8
5.3 Working LOHC material	8
5.3.1 General	8
5.3.2 LOHC-H material	9
5.3.3 LOHC-D material	9
6 Test methods	10
6.1 General	10
6.2 Material properties	10
6.3 Further substances	10
Annex A (normative) Nominal material properties of the described LOHC systems	12
Annex B (informative) Definition of LOHC side products/other hydrocarbons	13
Annex C (informative) Example for the determination of the degree of hydrogenation	14
Annex D (informative) Exemplary test protocol and retention times for purity and hydrocarbon analysis	15
Bibliography	16

Figures

Figure 1 — General concept of the LOHC-technology	7
---	---

Tables

Table 1 — LOHC-0 material properties at 20 °C	8
Table 2 — Limits for contamination of LOHC-0 material	8
Table 3 — LOHC-H material properties at 20 °C	9
Table 4 — Limits for contamination of LOHC-H material	9
Table 5 — LOHC-D material properties at 20 °C	9
Table 6 — Limits for contamination of LOHC-D material	10
Table A.1 — Nominal values of density in regard to the degree of hydrogenation (DoH) (properties at 20 °C)	12
Table A.2 — Nominal values of dynamic viscosity in regard to the degree of hydrogenation (DoH) (properties at 20 °C)	12