DIN SAE SPEC 91471:2023-05 (E)

Assessment methodology for automotive LiDAR sensors; Text in English

Inhalt

Seite

Foreword 5
Introduction 7
1 Scope 8
2 Normative references 8
3 Terms and definitions 8
4 Symbols and abbreviations 14
5 Overall methodology 16
6 Common specification of LiDAR sensors 17
6.1 Overview 17
6.2 Category: Device data 17
6.3 Category: Physical properties 18
6.4 Category: Installation specification 19
6.5 Category: Power supply 20
6.6 Category: Ingress protection 20
6.7 Category: Detection system 21
6.7.1 Transmitter 21
6.7.2 Receiver 22
6.8 Category: Basic detection properties 22
7 Assessment methodology 23
7.1 Overview 23
7.2 Evaluation metrics 23
7.2.1 Detection distance 23
7.2.2 Resolution 23
7.2.3 False-positive detection 24
7.2.4 Spatial error 25
7.2.5 Separability 26
7.3 Evaluation tools 27
7.4 Test scenarios 29
7.4.1 Overview 29
7.4.2 Multi-domain test 30
7.4.3 Angular separability 33
7.4.4 Radial separability 1 36
7.4.5 Radial separability 2 38
7.4.6 False alarm rate 1 40
7.4.7 False alarm rate 2 41
7.4.8 Cross-domain test 43
7.5 Documentation 46
Annex A (informative) Background to clustering 47
Bibliography 48

Figures

Figure 1 — True-positive and false-positive space **10**

Figure 2 — Clustering **11**

Figure 3 — Accuracy and precision **13**

Figure 4 — Binary feature separability **14**

Figure 5 — From environment perception to object data **17**

Figure 6 — LiDAR point clouds for a) pedestrian target and b) vehicle target **17**

Figure 7 — Representation of angular cluster density **24**

Figure 8 — Representation of absolute angular deviations of false-positive clusters **25**

Figure 9 — Schematic representation of Lambertian target of size 1 m × 1 m on target holder **28**

Figure 10 — Sensor mounting platform with two rotation stages (azimuth and elevation) **28**

Figure 11 — Angular offsets for variation of sensor pose in azimuth and elevation **29**

Figure 12 — Schematic representation of sensor and target for multi-domain test **30**

Figure 13 — Differentiation of true-positive clusters and false-positive clusters **32**

Figure 14 — Angular separability **34**

Figure 15 — Angular separability test setup **34**

Figure 16 — Radial separability test setup **36**

Figure 17 — Radial separability test setup with see-through object between sensor and target **38**

Figure 18 — False alarm rate 1 test setup **40**

Figure 19 — False alarm rate 2 test setup **42**

Figure 20 — Sensor aperture position within full width half maximum beam of light source **43**

Figure 21 — 2-D representation of cross-domain test in angular plane **44**

Figure 22 — Top-view of cross-domain test setup **45**

Tables

Table 1 — Clustering map **11**

Table 2 — Variations for multi-domain test **31**

Table 3 — Variations for angular separability test **35**

Table 4 — Variations for radial separability 1 test **37**

Table 5 — Variations for radial separability 2 test **39**