

DIN SPEC 91533:2026-04 (E)

Battery swapping systems for electric heavy-duty vehicles for range extension; Text in English

Contents

| | Page |
|---|------|
| Foreword | 5 |
| Introduction..... | 7 |
| 1 Scope..... | 8 |
| 2 Normative references | 8 |
| 3 Terms and definitions..... | 9 |
| 4 Abbreviations | 10 |
| 5 General information | 10 |
| 5.1 General..... | 10 |
| 5.2 System components' nomenclatura | 10 |
| 5.3 Depth of standardization | 12 |
| 5.4 Full and partial battery swap | 13 |
| 5.5 Targeted vehicles | 13 |
| 5.6 Battery position | 13 |
| 5.7 Drive position | 14 |
| 5.8 Vehicle Coordinate System..... | 14 |
| 5.9 Battery swapping station coordinate system..... | 14 |
| 6 Specific requirements | 15 |
| 6.1 Standard Infrastructure Interface (SII) only vehicles | 15 |
| 6.1.1 General..... | 15 |
| 6.1.2 Package..... | 15 |
| 6.1.3 Modularity | 16 |
| 6.1.4 Access | 16 |
| 6.1.5 Centering system | 17 |
| 6.1.6 Fastening system | 17 |
| 6.1.7 Contacting system | 18 |
| 6.1.8 Thermal management..... | 19 |
| 6.1.9 Safety/security..... | 19 |
| 6.2 Standard Battery Housing (SBH)..... | 20 |
| 6.2.1 General..... | 20 |
| 6.2.2 Package..... | 20 |
| 6.2.3 Modularity | 21 |
| 6.2.4 Access | 21 |
| 6.2.5 Centering system | 21 |
| 6.2.6 Fastening system | 22 |
| 6.2.7 Contacting system | 22 |
| 6.2.8 Thermal management system..... | 22 |
| 6.2.9 Safety/security | 23 |
| Annex A (informative) Exemplary Implementation | 24 |
| A.1 UniSwapHD implementation | 24 |
| A.1.1 General..... | 24 |
| A.1.2 Modularity | 24 |
| A.1.3 Centering system | 24 |
| A.1.4 Fastening system | 25 |

| | | |
|-------|---|----|
| A.1.5 | Definitions for contacting interface between each swappable battery system and the vehicle..... | 25 |
| A.1.6 | Design and centering system for contacting interface..... | 25 |
| A.1.7 | Thermal management system..... | 26 |
| A.2 | Qiji Solution..... | 27 |
| A.2.1 | General | 27 |
| A.2.2 | Package..... | 27 |
| A.2.3 | Modularity | 27 |
| A.2.4 | Fastening system | 28 |
| A.2.5 | Definitions for contacting interface between each swappable battery system and the vehicle..... | 29 |
| A.2.6 | Design and centering system for contacting interface..... | 30 |
| | Bibliography..... | 31 |

Figures

| | | |
|------------|---|----|
| Figure 1 | — Nomenclatura, battery swapping ecosystem..... | 11 |
| Figure 2 | — Nomenclatura, vehicle-sided systems..... | 12 |
| Figure 3 | — Overview over different depth of standardization for swappable battery system and BSU | 13 |
| Figure 4 | — Vehicle coordinate system..... | 14 |
| Figure 5 | — Swapping station coordinate system | 15 |
| Figure 6 | — Vehicle swapping unit dimensions | 16 |
| Figure 7 | — Exemplary layout definition of screwhead position (bottom view) | 18 |
| Figure A.1 | — Example of two module configuration..... | 24 |
| Figure A.2 | — Exemplary layout definition (bottom view)..... | 25 |
| Figure A.3 | — Concept contacting design | 26 |
| Figure A.4 | — Basic structure of cooling system..... | 27 |
| Figure A.5 | — Example of three module configuration..... | 28 |
| Figure A.6 | — Exemplary layout definition (bottom view)..... | 29 |
| Figure A.7 | — Connector Interface design..... | 30 |

Tables

| | | |
|-----------|---|----|
| Table 1 | — Technical parameters of the vehicle swapping unit for SII | 16 |
| Table 2 | — Technical parameters of the vehicle swapping unit for SBH | 21 |
| Table A.1 | — Overview of tolerances in the vehicle to station positioning system | 24 |
| Table A.2 | — Technical parameters of the vehicle swapping unit | 27 |