ISO/IEC 29341-6-13:2008-11 (E)

Information technology_- UPnP Device Architecture_- Part_6-13: Heating, Ventilation, and Air Conditioning Device Control Protocol_- House Status Service

CONTENTS

FOREWORD 4

ORIGINAL UPNP DOCUMENTS (informative) 6

1. Overview and Scope 8

2. Service Modeling Definitions 9

2.1. Service Type 9

2.2. State Variables 9

2.2.1. OccupancyState 9
2.2.2. ActivityLevel 9
2.2.3. DormancyLevel 10
2.2.4. Relationships Between State Variables 10

2.3. Eventing and Moderation 11

2.3.1. Event Model 11

2.4. Actions 12

2.4.1. GetOccupancyState 12
2.4.2. GetActivityLevel 12
2.4.3. GetDormancyLevel 13
2.4.4. SetOccupancyState 13
2.4.5. SetActivityLevel 14
2.4.6. SetDormancyLevel 14
2.4.7. Non-Standard Actions Implemented by a UPnP Vendor 15
2.4.8. Common Error Codes 15

2.5. Theory of Operation 16

2.6. Synchronization of Multiple Instances 16

3. XML Service Description 18

4. Test 20

LIST OF TABLES

Table 1: State Variables 9

Table 2: AllowedValueList for ActivityLevel 10

Table 3: DefaultValue for ActivityLevel 10

Table 4: AllowedValueList for DormancyLevel 10

Table 5: DefaultValue for DormancyLevel 10

Table 6: Event Moderation 11

Table 7: Actions 12

Table 8: Arguments for GetOccupancyState 12

Table 9: Arguments for GetActivityLevel 12

Table 10: Arguments for GetDormancyLevel 13

Table 11: Arguments for SetOccupancyState 13

Table 12: Arguments for SetActivityLevel 14

Table 13: Arguments for SetDormancyLevel 14

Table 14: Common Error Codes 15