

ISO/IEC 29341-8-12:2008-11 (E)

Information technology_ - UPnP Device Architecture_ - Part_8-12: Internet Gateway Device Control Protocol_ - Link Authentication Service

CONTENTS

- FOREWORD4
- ORIGINAL UPNP DOCUMENTS (informative)6
- 1. Overview and Scope8**
- 2. Service Modeling Definitions9**
 - 2.1. ServiceType9
 - 2.2. State Variables9
 - 2.2.1. NumberOfEntries9
 - 2.2.2. Identifier9
 - 2.2.3. Secret10
 - 2.2.4. SecretType10
 - 2.2.5. AuthType11
 - 2.2.6. AuthState11
 - 2.2.7. CredentialState12
 - 2.2.8. Description12
 - 2.2.9. MACAddress12
 - 2.2.10. CredentialDuration13
 - 2.2.11. LinkedIdentifier13
 - 2.2.12. LastChange13
 - 2.2.13. LastError14
 - 2.3. Eventing and Moderation14
 - 2.3.1. Event Model14
 - 2.4. Actions16
 - 2.4.1. GetGenericEntry17
 - 2.4.2. GetSpecificEntry18
 - 2.4.3. AddEntry19
 - 2.4.4. UpdateEntry20
 - 2.4.5. DeleteEntry21
 - 2.4.6. GetNumberOfEntries22
 - 2.4.7. FactoryDefaultReset22
 - 2.4.8. ResetAuthentication23
 - 2.4.9. Common Error Codes23
 - 2.5. Theory of Operation24
 - 2.5.1. 802.1x introduction24
 - 2.5.2. High level intended operation24
 - 2.5.3. Detailed level operation25
 - 2.5.4. Record format26
 - 2.5.5. Example using client certificate credentials27
 - 2.5.6. Limitations on Pending Records27
- 3. XML Service Description28**
- 4. Test33**

LIST OF TABLES

Table 1: State Variables	9
Table 1.1: allowedValueList for SecretType.....	10
Table 1.2: allowedValueList for AuthType.....	11
Table 1.3: allowedValueList for AuthState.....	11
Table 1.4: allowedValueList for CredentialState.....	12
Table 2: Event Moderation	14
Table 3: Actions	16
Table 4: Arguments for GetGenericEntry	17
Table 5: Arguments for GetSpecificEntry	18
Table 6: Arguments for AddEntry.....	19
Table 7: Arguments for UpdateEntry	20
Table 8: Arguments for DeleteEntry	21
Table 9: Arguments for GetNumberOfEntries.....	22
Table 10: Common Error Codes	23