ISO/IEC 29341-8-13:2008-11 (E)

Information technology_- UPnP Device Architecture_- Part_8-13: Internet Gateway Device Control Protocol_- Radius Client Service

CONTENTS

FOREWORD 3
ORIGINAL UPNP DOCUMENTS (informative) 5
1. Overview and Scope 7
2. Service Modeling Definitions 7
2.1. ServiceType 7
2.2. State Variables 7
2.2.1. NumberOfAuthServerEntries 7
2.2.2. AuthServerIPAddress 8
2.2.3. AuthServerPortNumber 8
2.2.4. AuthServerSharedSecret 8
2.3. Eventing and Moderation 8
2.3.1. Event Model 8
2.4. Actions 8
2.4.1. GetGenericAuthServerEntry 9
2.4.2. GetSpecificAuthServerEntry 9
2.4.3. AddAuthServerEntry 10
2.4.4. DeleteAuthServerEntry 11
2.4.5. FactoryDefaultReset 11
2.4.6. ResetAuthentication 11
2.4.7. Non-Standard Actions Implemented by a UPnP Device Vendor 12
2.4.8. Common Error Codes 12
2.5. Theory of Operation 12
2.5.1. Operation of the RADIUS Client 12
3. XML Service Description 13
4. Test 15

LIST OF TABLES

Table 1: State Variables 7
Table 2: Event Moderation 8
Table 3: Actions 8
Table 4: Arguments for GetGenericAuthServerEntry 9
Table 5: Arguments for GetSpecificAuthServerEntry 9
Table 6: Arguments for AddAuthServerEntry 10
Table 7: Arguments for DeleteAuthServerEntry 11
Table 8: Common Error Codes 12