

# ISO/IEC 29341-8-13:2008-11 (E)

## Information technology\_ - UPnP Device Architecture\_ - Part\_8-13: Internet Gateway Device Control Protocol\_ - Radius Client Service

---

### CONTENTS

FOREWORD .....	3
ORIGINAL UPNP DOCUMENTS (informative) .....	5
<b>1. Overview and Scope .....</b>	<b>7</b>
<b>2. Service Modeling Definitions .....</b>	<b>7</b>
2.1. ServiceType .....	7
2.2. State Variables .....	7
2.2.1. NumberOfAuthServerEntries .....	7
2.2.2. AuthServerIPAddress .....	8
2.2.3. AuthServerPortNumber .....	8
2.2.4. AuthServerSharedSecret .....	8
2.3. Eventing and Moderation .....	8
2.3.1. Event Model .....	8
2.4. Actions .....	8
2.4.1. GetGenericAuthServerEntry .....	9
2.4.2. GetSpecificAuthServerEntry .....	9
2.4.3. AddAuthServerEntry .....	10
2.4.4. DeleteAuthServerEntry .....	11
2.4.5. FactoryDefaultReset .....	11
2.4.6. ResetAuthentication .....	11
2.4.7. Non-Standard Actions Implemented by a UPnP Device Vendor .....	12
2.4.8. Common Error Codes .....	12
2.5. Theory of Operation .....	12
2.5.1. Operation of the RADIUS Client .....	12
<b>3. XML Service Description .....</b>	<b>13</b>
<b>4. Test .....</b>	<b>15</b>

### LIST OF TABLES

Table 1: State Variables .....	7
Table 2: Event Moderation .....	8
Table 3: Actions .....	8
Table 4: Arguments for GetGenericAuthServerEntry .....	9
Table 5: Arguments for GetSpecificAuthServerEntry .....	9
Table 6: Arguments for AddAuthServerEntry .....	10
Table 7: Arguments for DeleteAuthServerEntry .....	11
Table 8: Common Error Codes .....	12