

# ISO/IEC 29341-9-10:2008-11 (E)

## Information technology\_ - UPnP Device Architecture\_ - Part\_9-10: Imaging Device Control Protocol\_ - External Activity Service

---

### CONTENTS

- FOREWORD ..... 3
- ORIGINAL UPNP DOCUMENTS (informative) ..... 5
- 1. Overview and Scope ..... 7**
- 2. Service Modeling Definitions ..... 8**
  - 2.1. ServiceType ..... 8
  - 2.2. Service State Table ..... 8
    - 2.2.1. Activity ..... 8
    - 2.2.2. AvailableRegistrations ..... 8
    - 2.2.3. DisplayString ..... 9
    - 2.2.4. DisplayStringSize ..... 9
    - 2.2.5. ButtonName ..... 9
    - 2.2.6. Duration ..... 9
    - 2.2.7. RegistrationID ..... 10
  - 2.3. Eventing and Moderation ..... 10
  - 2.4. Actions ..... 11
    - 2.4.1. Register ..... 11
    - 2.4.2. Renew ..... 12
    - 2.4.3. Unregister ..... 12
    - 2.4.4. Common Error Codes ..... 13
  - 2.5. Theory of Operation ..... 13
    - 2.5.1. Interactions with an Associated Service ..... 13
- 3. XML Service Description ..... 16**
- 4. Testing ..... 19**
  - 4.1. Issues ..... 19
  - 4.2. Syntax Testing ..... 19
    - 4.2.1. Register Action Tests ..... 19
    - 4.2.2. Renew Action Tests ..... 19
    - 4.2.3. Unregister Action Tests ..... 19

### LIST OF TABLES

- Table 1: Service State Table ..... 8
- Table 1.1: DisplayStringSize allowedValueRange ..... 9
- Table 1.2: ButtonPress allowed values ..... 9
- Table 1.3: Duration allowed values ..... 9
- Table 2: Evented Variables ..... 10
- Table 3: Actions ..... 11
- Table 4: Arguments for Register ..... 11
- Table 5: Arguments for Renew ..... 12
- Table 6: Arguments for Unregister ..... 12
- Table 7: Common Error Codes ..... 13