ISO/IEC 29341-10-1:2008-11 (E)

Information technology_- UPnP Device Architecture_- Part_10-1: Quality of Service Device Control Protocol_- Quality of Service Architecture

CONTENTS

FOREWORD 4
ORIGINAL UPNP DOCUMENTS (informative) 6
1. Glossary 8
2. Introduction 11
2.1. Referenced Specifications 11
3. Architecture Overview 12
3.1. Motivation 13
3.1.1. Policy Management 13
3.2. Key Concepts 13
3.2.1. Admission Control 13
3.2.2. Admission Policy 14
3.2.3. Traffic Descriptor 14
4. UPnP QoS Components 15
4.1. QosPolicyHolder Service 15
4.1.1. Role 15
4.1.2. Traffic Stream QoS Policy Description 15
4.2. QoS Manager 16
4.2.1. Role 16
4.2.2. Behavior 16
4.2.3. Dealing with Policy 16
4.2.4. QoS Update 17
4.3. QosDevice Service 17
4.3.1. Role 17
4.3.2. Behavior 17
4.3.3. Setup Traffic QoS 17
4.3.4. Traffic Admission Control 17
4.3.5. Path Information 18
5. System Operation 19
5.1. Initiation of QoS Setup 19
5.1.1. Generic Control Point 19
5.1.2. Independent AV Control Point 20
5.1.3. Determination of TrafficId 20
5.1.4. Creation of Optional Traffic Specification (Tspec) 21
5.2. Determination of Policy for the Traffic Stream 21
5.2.1. QosPolicyHolder Service 21
5.2.2. Default Policy 21
5.3. Determination of QosDevice Services that should be configured 22
5.3.1. Path Determination (Optional) 22
5.3.2. Setup Capabilities Determination 22
5.4. Configuration of QoS Devices 22
5.4.1. Priority Setup Strategy 23
5.4.2. Admission Control Strategy 23

5.5. Run time Operation 23
5.5.1. Lease Management 23
5.5.2. Traffic revocation 23
5.5.3. Violation of TSPEC 23
5.5.4. The Use of Traffic Descriptor 23
5.6. Relationship to other UPnP Services and non UPnP Traffic Streams 23
5.6.1. UPnP IGD 23
5.6.2. Legacy Devices 24
6. Prioritized QoS 25
6.1. Management of Packet Priorities 25
7. Parameterized QoS 27
Annex A (normative) **Layer 2 Implementation Guidelines 28**
A.1 802.1p and 802.1d, Annex G 28
A.2 HomePlug 28
A.3 HPNA 2.0 29