ISO/IEC 29341-10-11:2008-11 (E)

Information technology_- UPnP Device Architecture_- Part_10-11: Quality of Service Device Control Protocol_- Quality of Service Manager Service

CONTENTS

FOREWORD 4
ORIGINAL UPNP DOCUMENTS (informative) 6
1. Overview and Scope 8
1.1. Referenced Specifications 8
2. Service Modeling Definitions 9
2.1. ServiceType 9
2.2. State Variables 9
2.2.2. A_ARG_TYPE_TrafficDescriptor 10
2.2.3. A_ARG_TYPE_TrafficHandle 15
2.2.4. A_ARG_TYPE_NumTrafficDescriptors 15
2.2.5. A_ARG_TYPE_NumPolicyHolders 15
2.2.6. A_ARG_TYPE_ ListOfTrafficDescriptors 15
2.2.7. Relationships Between State Variables 16
2.3. Eventing and Moderation 17
2.3.1. Event Model 17
2.4. Actions 18
2.4.1 RequestTrafficQos 18
2.4.2. UpdateTrafficQos 21
2.4.3. ReleaseTrafficQos 23
2.4.4. BrowseAllTrafficDescriptors 23
2.4.5. Non-Standard Actions Implemented by a UPnP Vendor 24
2.4.6. Relationships Between Actions 25
2.4.7. Common Error Codes 25
2.5. Theory of Operation 27
3. XML Service Description 29
4. Test 31
Annex A (normative) **TrafficDescriptor XML Schema 32**
Annex B (normative) **Traffic Descriptor Matrix 39**

LIST OF TABLES

Table 2-1: State Variables 10
Table 2-2: Event Moderation 17
Table 2-3: Actions 18
Table 2-4: Arguments for RequestTrafficQos 18
Table 2-5: Error Codes for RequestTrafficQos 20
Table 2-6: Arguments for UpdateTrafficQos 21
Table 2-7: Error Codes for UpdateTrafficQos 22
Table 2-8: Arguments for ReleaseTrafficQos 23
Table 2-9: Error Codes for ReleaseTrafficQos 23
Table 2-10: Arguments for BrowseAllTrafficDescriptors 23
Table 2-11: Error Codes for BrowseAllTrafficDescriptors 24
Table 2-12: Common Error Codes 25