

ISO/IEC 29341-12-11:2008-11 (E)

Information technology_ - UPnP Device Architecture_ - Part_12-11: Remote User Interface Device Control Protocol_ - Remote User Interface Server Service

CONTENTS

FOREWORD	3
ORIGINAL UPNP DOCUMENTS (informative)	5
1. Overview and Scope	7
2. Service Modeling Definitions	8
2.1. ServiceType	8
2.2. State Variables	8
2.2.1. UIListingUpdate	8
2.2.2. A_ARG_TYPE_DeviceProfile	8
2.2.3. A_ARG_TYPE_URI	8
2.2.4. A_ARG_TYPE_CompatibleUIs	9
2.2.5. A_ARG_TYPE_String	9
2.2.6. A_ARG_TYPE_Int	9
2.3. Eventing and Moderation	9
2.4. Actions	10
2.4.1. GetCompatibleUIs	10
2.4.2. SetUILifetime	11
2.4.3. Non-Standard Actions Implemented by a UPnP Vendor	12
2.4.4. Relationships Between Actions	12
2.4.5. Common Error Codes	12
3. Theory of Operation	13
3.1. Example Values of State Variables	13
3.1.1. A_ARG_TYPE_URI	13
3.1.2. A_ARG_TYPE_CompatibleUIs	13
3.1.3. A_ARG_TYPE_DeviceProfile	17
3.1.4. UIListingUpdate	18
3.1.5. UIFilter Examples	18
4. A_ARG_TYPE_CompatibleUIs XSD Schema	19
5. DeviceProfile XSD Schema	20
6. XML Service Description	21

LIST OF TABLES

Table 1: Service State Variables	8
Table 2: Event moderation	9
Table 3: Actions	10
Table 4: Arguments for GetCompatibleUIs ()	10
Table 5: Arguments for SetUILifetime ()	11
Table 6: Common Error Codes	12
Table 7: shortName values for known remoting protocols	16