ISO/IEC 14776-453:2009-12 (E)

Information technology_- Small computer system interface (SCSI)_- Part_453: Primary commands-3 (SPC-3)

Contents

Page

Introduction ... 23

1 Scope ... 24

2 Normative references ... 25
2.1 General ... 25
2.2 Approved references ... 25
2.3 IETF References ... 27

3 Terms and definitions, symbols, abbreviations and conventions ... 28
3.1 Terms and definitions ... 28
3.2 Acronyms ... 39
3.3 Keywords ... 40
3.4 Conventions ... 41
3.5 Bit and byte ordering ... 42
3.6 Notation conventions ... 43
3.6.1 Notation for byte encoded character strings ... 43
3.6.2 Notation for procedure calls ... 44
3.6.3 Notation for state diagrams ... 45
3.6.4 Notation for binary power multipliers ... 45

4 General Concepts ... 46
4.1 Introduction ... 46
4.2 The request-response model ... 46
4.3 The Command Descriptor Block (CDB) ... 46
4.3.1 CDB usage and structure ... 46
4.3.2 The fixed length CDB formats ... 47
4.3.3 The variable length CDB formats ... 49
4.3.4 Common CDB fields ... 50
4.3.4.1 Operation code ... 50
4.3.4.2 Service action ... 51
4.3.4.3 Logical block address ... 51
4.3.4.4 Transfer length ... 51
4.3.4.5 Parameter list length ... 52
4.3.4.6 Allocation length ... 52
4.3.4.7 Control ... 52
4.4 Data field requirements ... 52
4.4.1 ASCII data field requirements ... 52
4.4.2 Null data field termination and zero padding requirements ... 52
4.5 Sense data ... 53
4.5.1 Sense data introduction ... 53
4.5.2 Descriptor format sense data ... 54
4.5.2.1 Descriptor format sense data overview ... 54
4.5.2.2 Information sense data descriptor ... 55
4.5.2.3 Command-specific information sense data descriptor ... 56
4.5.2.4 Sense key specific sense data descriptor ... 57
4.5.2.4.1 Sense key specific sense data descriptor introduction ... 57
4.5.2.4.2 Field pointer sense key specific data ... 57
4.5.2.4.3 Actual retry count sense key specific data ... 58
4.5.2.4.4 Progress indication sense key specific data ... 59
4.5.2.4.5 Segment pointer sense key specific data ... 59
4.5.2.5 Field replaceable unit sense data descriptor ... 60
4.5.2.6 Vendor specific sense data descriptors ... 60
4.5.3 Fixed format sense data ... 61
4.5.4 Current errors ... 62
4.5.5 Deferred errors ... 62
4.5.6 Sense key and sense code definitions ... 63

5 Model common to all device types 78
5.1 Introduction to the model common to all device types 78
5.2 Important commands for all SCSI device servers 78
5.2.1 Commands implemented by all SCSI device servers 78
5.2.2 Commands recommended for all SCSI device servers 78
5.2.3 Using the INQUIRY command 78
5.2.4 Using the REPORT LUNS command 78
5.2.5 Using the TEST UNIT READY command 78
5.2.6 Using the REQUEST SENSE command 78
5.3 Implicit head of queue 79
5.4 Parameter rounding 79
5.5 Self-test operations 79
5.5.1 Default self-test 79
5.5.2 The short and extended self-tests 79
5.5.3 Self-test modes 80
5.5.3.1 Self-test modes overview 80
5.5.3.2 Foreground mode 80
5.5.3.3 Background mode 80
5.5.3.4 Features common to foreground and background self-test modes 81
5.6 Reservations 82
5.6.1 Persistent Reservations overview 82
5.6.2 Third party persistent reservations 86
5.6.3 Exceptions to SPC-2 RESERVE and RELEASE behavior 86
5.6.4 Preserving persistent reservations and registrations 87
5.6.4.1 Preserving persistent reservations and registrations through power loss 87
5.6.4.2 Nonvolatile memory considerations for preserving persistent reservations and registrations 87
5.6.5 Finding persistent reservations and reservation keys 88
5.6.5.1 Summary of commands for finding persistent reservations and reservation keys 88
5.6.5.2 Reporting reservation keys 88
5.6.5.3 Reporting the persistent reservation 88
5.6.5.4 Reporting full status 89
5.6.6 Registering 89
5.6.7 Registering and moving the reservation 93
5.6.8 Reserving 94
5.6.9 Persistent reservation holder 95
5.6.10 Releasing persistent reservations and removing registrations 95
5.6.10.1 Overview 95
5.6.10.1.1 Summary of service actions that release persistent reservations and remove registrations 95
5.6.10.1.2 Processing for released Registrants Only persistent reservations 96
5.6.10.1.3 Processing for released All Registrants persistent reservations 97
5.6.10.1.4 Processing for other released persistent reservations 97
5.6.10.2 Releasing 97
5.6.10.3 Unregistering 98
5.6.10.4 Preempting 98
5.6.10.4.1 Overview 98
5.6.10.4.2 Failed persistent reservation preempt 100
5.6.10.4.3 Preempting persistent reservations and registration handling 100
5.6.10.4.4 Removing registrations 101
5.6.10.5 Preempting and aborting 101
5.6.10.6 Clearing 102
5.7 Multiple target port and initiator port behavior 102
5.8 Target port group access states 103
5.8.1 Target port group access overview 103
5.8.2 Asymmetric logical unit access 103
5.8.2.1 Introduction to asymmetric logical unit access 103
5.8.2.2 Explicit and implicit asymmetric logical unit access 104
5.8.2.3 Discovery of asymmetric logical unit access behavior 104
5.8.2.4 Target port asymmetric access states 104
5.8.2.4.1 Target port asymmetric access states overview 104
5.8.2.4.2 Active/optimized state 104

5.8.2.4.3 Active/non-optimized state 105
5.8.2.4.4 Standby state 105
5.8.2.4.5 Unavailable state 106
5.8.2.5 Transitions between target port asymmetric access states 106
5.8.2.6 Preference Indicator 107
5.8.2.7 Implicit asymmetric logical units access management 107
5.8.2.8 Explicit asymmetric logical units access management 108
5.8.2.9 Behavior after power on, hard reset, logical unit reset, and I_T nexus loss 108
5.8.3 Symmetric logical unit access 108
5.9 Power conditions 108
5.9.1 Power conditions overview 108
5.9.2 Power condition state machine 109
5.9.2.1 Power condition state machine overview 109
5.9.2.2 PC0:Powered_on state 110
5.9.2.3 PC1:Active state 110
5.9.2.4 PC2:Idle state 111
5.9.2.5 PC3:Standby state 111
5.10 Removable medium devices with an attached medium changer 111
5.11 Medium auxiliary memory 111
5.12 Application client logging 112
5.13 Device clocks 113

6 Commands for all device types 114
6.1 Summary of commands for all device types 114
6.2 CHANGE ALIASES command 116
6.2.1 CHANGE ALIASES command introduction 116
6.2.2 Alias entry format 118
6.2.3 Alias designation validation 119
6.2.4 Alias entry protocol independent designations 119
6.2.4.1 Alias entry protocol independent designations overview 119
6.2.4.2 NULL DESIGNATION alias format 119
6.3 EXTENDED COPY command 120
6.3.1 EXTENDED COPY command introduction 120
6.3.2 Errors detected before starting processing of the segment descriptors 123
6.3.3 Errors detected during processing of segment descriptors 123
6.3.4 Abort task management functions 125
6.3.5 Descriptor type codes 125
6.3.6 Target descriptors 127
6.3.6.1 Target descriptors introduction 127
6.3.6.2 Identification descriptor target descriptor format 129
6.3.6.3 Alias target descriptor format 130
6.3.6.4 Device type specific target descriptor parameters for block device types 130
6.3.6.5 Device type specific target descriptor parameters for sequential-access device types 131
6.3.6.6 Device type specific target descriptor parameters for processor device types 132
6.3.7 Segment descriptors 132
6.3.7.1 Segment descriptors introduction 132
6.3.7.2 Segment descriptor processing 133
6.3.7.3 Block device to stream device operations 137
6.3.7.4 Stream device to block device operations 138
6.3.7.5 Block device to block device operations 139
6.3.7.6 Stream device to stream device operations 141
6.3.7.7 Inline data to stream device operation 142
6.3.7.8 Embedded data to stream device operation 144
6.3.7.9 Stream device to discard operation 145
6.3.7.10 Verify device operation 146
6.3.7.11 Block device with offset to stream device operation 147
6.3.7.12 Stream device to block device with offset operation 148
6.3.7.13 Block device with offset to block device with offset operation 149
6.3.7.14 Write filemarks operation 150
6.3.7.15 Space operation 151

6.3.7.16 Locate operation 152
6.3.7.17 Tape device image copy operation 153
6.3.7.18 Register persistent reservation key operation 154
6.3.7.19 Third party persistent reservations source I_T nexus 154
6.4 INQUIRY command 157
6.4.1 INQUIRY command introduction 157
6.4.2 Standard INQUIRY data 158
6.4.3 SCSI Parallel Interface specific INQUIRY data 162
6.4.4 Vital product data 163
6.5 LOG SELECT command 165
6.6 LOG SENSE command 167
6.7 MODE SELECT(6) command 169
6.8 MODE SELECT(10) command 171
6.9 MODE SENSE(6) command 171
6.9.1 MODE SENSE(6) command introduction 171
6.9.2 Current values 173
6.9.3 Changeable values 173
6.9.4 Default values 173
6.9.5 Saved values 173
6.9.6 Initial responses 173
6.10 MODE SENSE(10) command 174
6.11 PERSISTENT RESERVE IN command 175
6.11.1 PERSISTENT RESERVE IN command introduction 175
6.11.2 READ KEYS service action 176
6.11.3 READ RESERVATION service action 176
6.11.3.1 READ RESERVATION service action introduction 176
6.11.3.2 Format of PERSISTENT RESERVE IN parameter data for READ RESERVATION 177
6.11.3.3 Persistent reservations scope 178
6.11.3.4 Persistent reservations type 178
6.11.4 REPORT CAPABILITIES service action 179
6.11.5 READ FULL STATUS service action 180
6.12 PERSISTENT RESERVE OUT command 182
6.12.1 PERSISTENT RESERVE OUT command introduction 182
6.12.2 PERSISTENT RESERVE OUT service actions 184
6.12.3 Basic PERSISTENT RESERVE OUT parameter list 185
6.12.4 PERSISTENT RESERVE OUT command with REGISTER AND MOVE service action parameters 188
6.13 PREVENT ALLOW MEDIUM REMOVAL command 190
6.14 READ ATTRIBUTE command 191
6.14.1 READ ATTRIBUTE command introduction 191
6.14.2 ATTRIBUTE VALUES service action 192
6.14.3 ATTRIBUTE LIST service action 193
6.14.4 VOLUME LIST service action 194
6.14.5 PARTITION LIST service action 194
6.15 READ BUFFER command 195
6.15.1 READ BUFFER command introduction 195
6.15.2 Combined header and data mode (00h) 196
6.15.3 Vendor specific mode (01h) 196
6.15.4 Data mode (02h) 196
6.15.5 Descriptor mode (03h) 196
6.15.6 Echo buffer mode (0Ah) 197
6.15.7 Echo buffer descriptor mode (0Bh) 198
6.15.8 Enable expander communications protocol and Echo buffer (1Ah) 198
6.16 READ MEDIA SERIAL NUMBER command 199
6.17 RECEIVE COPY RESULTS command 200
6.17.1 RECEIVE COPY RESULTS command introduction 200
6.17.2 COPY STATUS service action 201
6.17.3 RECEIVE DATA service action 203
6.17.4 OPERATING PARAMETERS service action 204
6.17.5 FAILED SEGMENT DETAILS service action 207
6.18 RECEIVE DIAGNOSTIC RESULTS command 208

6.19 REPORT ALIASES command 209
6.20 REPORT DEVICE IDENTIFIER command 210
6.21 REPORT LUNS command 212
6.22 REPORT PRIORITY command 214
6.23 REPORT SUPPORTED OPERATION CODES command 216
6.23.1 REPORT SUPPORTED OPERATION CODES command introduction 216
6.23.2 All_commands parameter data format 218
6.23.3 One_command parameter data format 219
6.24 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command 220
6.25 REPORT TARGET PORT GROUPS command 222
6.26 REPORT TIMESTAMP command 225
6.27 REQUEST SENSE command 226
6.28 SEND DIAGNOSTIC command 228
6.29 SET DEVICE IDENTIFIER command 230
6.30 SET PRIORITY command 231
6.31 SET TARGET PORT GROUPS command 233
6.32 SET TIMESTAMP command 236
6.33 TEST UNIT READY command 237
6.34 WRITE ATTRIBUTE command 237
6.35 WRITE BUFFER command 240
6.35.1 WRITE BUFFER command introduction 240
6.35.2 Combined header and data mode (00h) 241
6.35.3 Vendor specific mode (01h) 241
6.35.4 Data mode (02h) 241
6.35.5 Download microcode mode (04h) 242
6.35.6 Download microcode and save mode (05h) 242
6.35.7 Download microcode with offsets mode (06h) 242
6.35.8 Download microcode with offsets and save mode (07h) 243
6.35.9 Write data to echo buffer mode (0Ah) 244
6.35.10 Enable expander communications protocol and Echo buffer mode (1Ah) 244
6.35.11 Disable expander communications protocol mode (1Bh) 244
6.35.12 Download application log mode (1Ch) 244

7 Parameters for all device types 247
7.1 Diagnostic parameters 247
7.1.1 Diagnostic page format and page codes for all device types 247
7.1.2 Supported diagnostic pages 249
7.2 Log parameters 250
7.2.1 Log page structure and page codes for all device types 250
7.2.2 Application Client log page 254
7.2.3 Buffer Over-Run/Under-Run log page 255
7.2.4 Error counter log pages 257
7.2.5 Informational Exceptions log page 257
7.2.6 Last n Deferred Errors or Asynchronous Events log page 259
7.2.7 Last n Error Events log page 259
7.2.8 Non-Medium Error log page 259
7.2.9 Protocol Specific Port log page 259
7.2.10 Self-Test Results log page 261
7.2.11 Start-Stop Cycle Counter log page 263
7.2.12 Supported Log Pages log page 265
7.2.13 Temperature log page 266
7.3 Medium auxiliary memory attributes 268
7.3.1 Attribute format 268
7.3.2 Attribute identifier values 269
7.3.2.1 Attribute identifier values overview 269
7.3.2.2 Device type attributes 270
7.3.2.3 Medium type attributes 276
7.3.2.4 Host type attributes 277
7.4 Mode parameters 279
7.4.1 Mode parameters overview 279

7.4.2 Mode parameter list format 279
7.4.3 Mode parameter header formats 279
7.4.4 Mode parameter block descriptor formats 281
7.4.4.1 General block descriptor format 281
7.4.5 Mode page and subpage formats and page codes 282
7.4.6 Control mode page 284
7.4.7 Control Extension mode page 288
7.4.8 Disconnect-Reconnect mode page 289
7.4.9 Extended mode page 291
7.4.10 Extended Device-Type Specific mode page 292
7.4.11 Informational Exceptions Control mode page 292
7.4.12 Power Condition mode page 295
7.4.13 Protocol Specific Logical Unit mode page 296
7.4.14 Protocol Specific Port mode page 297
7.5 Protocol specific parameters 299
7.5.1 Protocol specific parameters introduction 299
7.5.2 Alias entry protocol specific designations 299
7.5.2.1 Introduction to alias entry protocol specific designations 299
7.5.2.2 Fibre Channel specific alias entry designations 299
7.5.2.2.1 Introduction to Fibre Channel specific alias entry designations 299
7.5.2.2.2 Fibre Channel world wide port name alias entry designation 300
7.5.2.2.3 Fibre Channel world wide port name with N_Port checking alias entry designation 300
7.5.2.3 RDMA specific alias entry designations 301
7.5.2.3.1 Introduction to RDMA specific alias entry designations 301
7.5.2.3.2 RDMA target port identifier alias entry designation 301
7.5.2.3.3 InfiniBand global identifier with target port identifier checking alias entry designation 302
7.5.2.4 Internet SCSI specific alias entry designations 302
7.5.2.4.1 Introduction to Internet SCSI specific alias entry designations 302
7.5.2.4.2 iSCSI name alias entry designation 303
7.5.2.4.3 iSCSI name with binary IPv4 address alias entry designation 303
7.5.2.4.4 iSCSI name with IPname alias entry designation 304
7.5.2.4.5 iSCSI name with binary IPv6 address alias entry designation 305
7.5.3 EXTENDED COPY protocol specific target descriptors 306
7.5.3.1 Introduction to EXTENDED COPY protocol specific target descriptors 306
7.5.3.2 Fibre Channel N_Port_Name EXTENDED COPY target descriptor format 306
7.5.3.3 Fibre Channel N_Port_ID EXTENDED COPY target descriptor format 307
7.5.3.4 Fibre Channel N_Port_ID with N_Port_Name checking EXTENDED COPY target descriptor format 308
7.5.3.5 SCSI Parallel T_L EXTENDED COPY target descriptor format 309
7.5.3.6 IEEE 1394 EUI-64 EXTENDED COPY target descriptor format 310
7.5.3.7 RDMA EXTENDED COPY target descriptor format 311
7.5.3.8 iSCSI binary IPv4 address EXTENDED COPY target descriptor format 312
7.5.3.9 SAS serial SCSI protocol target descriptor format 313
7.5.4 TransportID identifiers 313
7.5.4.1 Overview of TransportID identifiers 313
7.5.4.2 TransportID for initiator ports using SCSI over Fibre Channel 314
7.5.4.3 TransportID for initiator ports using a parallel SCSI bus 315
7.5.4.4 TransportID for initiator ports using SCSI over IEEE 1394 315
7.5.4.5 TransportID for initiator ports using SCSI over an RDMA interface 316
7.5.4.6 TransportID for initiator ports using SCSI over iSCSI 316
7.5.4.7 TransportID for initiator ports using SCSI over SAS Serial SCSI Protocol 318
7.6 Vital product data parameters 319
7.6.1 Vital product data parameters overview and page codes 319
7.6.2 ASCII Information VPD page 319
7.6.3 Device Identification VPD page 320
7.6.3.1 Device Identification VPD page overview 320
7.6.3.2 Device identification descriptor requirements 323
7.6.3.2.1 Identification descriptors for logical units other than well known logical units 323
7.6.3.2.2 Identification descriptors for well known logical units 323
7.6.3.2.3 Identification descriptors for SCSI target ports 323
7.6.3.2.3.1 Relative target port identifiers 323

7.6.3.2.3.2 Target port names or identifiers 324
7.6.3.2.4 Identification descriptors for SCSI target devices 324
7.6.3.3 Vendor specific identifier format 324
7.6.3.4 T10 vendor ID based format 325
7.6.3.5 EUI-64 based identifier format 325
7.6.3.5.1 EUI-64 based identifier format overview 325
7.6.3.5.2 EUI-64 identifier format 326
7.6.3.5.3 EUI-64 based 12-byte identifier format 326
7.6.3.5.4 EUI-64 based 16-byte identifier format 327
7.6.3.6 NAA identifier format 327
7.6.3.6.1 NAA identifier basic format 327
7.6.3.6.2 NAA IEEE Extended identifier format 328
7.6.3.6.3 NAA IEEE Registered identifier format 328
7.6.3.6.4 NAA IEEE Registered Extended identifier format 329
7.6.3.7 Relative target port identifier format 329
7.6.3.8 Target port group identifier format 330
7.6.3.9 Logical unit group identifier format 330
7.6.3.10 MD5 logical unit identifier format 331
7.6.3.11 SCSI name string identifier format 332
7.6.4 Extended INQUIRY Data VPD page 333
7.6.5 Management Network Addresses VPD page 334
7.6.6 Mode Page Policy VPD page 336
7.6.7 SCSI Ports VPD page 337
7.6.8 Software Interface Identification VPD page 340
7.6.9 Supported VPD pages 341
7.6.10 Unit Serial Number VPD page 341

8 Well known logical units 342
8.1 Model for well known logical units 342
8.2 REPORT LUNS well known logical unit 342
8.3 ACCESS CONTROLS well known logical unit 343
8.3.1 Access controls model 343
8.3.1.1 Access controls commands 343
8.3.1.2 Access controls overview 343
8.3.1.3 The access control list (ACL) 344
8.3.1.3.1 ACL overview 344
8.3.1.3.2 Access identifiers 345
8.3.1.3.3 Logical unit access control descriptors 345
8.3.1.4 Managing the ACL 346
8.3.1.4.1 ACL management overview 346
8.3.1.4.2 Authorizing ACL management 346
8.3.1.4.3 Identifying logical units during ACL management 347
8.3.1.4.4 Tracking changes in logical unit identification 347
8.3.1.5 Enrolling AccessIDs 347
8.3.1.5.1 Enrollment states 347
8.3.1.5.1.1 Summary of enrollment states 347
8.3.1.5.1.2 Not-enrolled state 348
8.3.1.5.1.3 Enrolled state 349
8.3.1.5.1.4 Pending-enrolled state 349
8.3.1.5.2 ACL LUN conflict resolution 349
8.3.1.6 Granting and revoking access rights 350
8.3.1.6.1 Non-proxy access rights 350
8.3.1.6.2 Proxy access 350
8.3.1.6.2.1 Proxy tokens 350
8.3.1.6.2.2 Proxy LUNs 351
8.3.1.7 Verifying access rights 351
8.3.1.8 The management identifier key 352
8.3.1.8.1 Management identifier key usage 352
8.3.1.8.2 Overriding the management identifier key 353
8.3.1.8.2.1 The OVERRIDE MGMT ID KEY service action 353

8.3.1.8.2.2 The override lockout timer 353
8.3.1.9 Reporting access control information 354
8.3.1.10 Access controls log 354
8.3.1.11 Interactions of access controls and other features 355
8.3.1.11.1 Task set management and access controls 355
8.3.1.11.2 Existing reservations and ACL changes 355
8.3.1.12 Access controls information persistence and memory usage requirements 356
8.3.1.13 Access identifier formats 357
8.3.1.13.1 Access identifier type 357
8.3.1.13.2 AccessID access identifiers 357
8.3.2 ACCESS CONTROL IN command 358
8.3.2.1 ACCESS CONTROL IN introduction 358
8.3.2.2 REPORT ACL service action 358
8.3.2.2.1 REPORT ACL introduction 358
8.3.2.2.2 REPORT ACL parameter data format 359
8.3.2.2.2.1 REPORT ACL parameter data introduction 359
8.3.2.2.2.2 Granted ACL data page format 360
8.3.2.2.2.3 Granted All ACL data page format 362
8.3.2.2.2.4 Proxy Tokens ACL data page format 362
8.3.2.3 REPORT LU DESCRIPTORS service action 363
8.3.2.3.1 REPORT LU DESCRIPTORS introduction 363
8.3.2.3.2 REPORT LU DESCRIPTORS parameter data format 364
8.3.2.4 REPORT ACCESS CONTROLS LOG service action 368
8.3.2.4.1 REPORT ACCESS CONTROLS LOG introduction 368
8.3.2.4.2 REPORT ACCESS CONTROLS LOG parameter data format 369
8.3.2.4.2.1 REPORT ACCESS CONTROLS LOG parameter data introduction 369
8.3.2.4.2.2 Key Overrides access controls log portion page format 370
8.3.2.4.2.3 Invalid Keys access controls log portion page format 371
8.3.2.4.2.4 ACL LUN Conflicts access controls log portion page format 372
8.3.2.5 REPORT OVERRIDE LOCKOUT TIMER service action 373
8.3.2.6 REQUEST PROXY TOKEN service action 374
8.3.3 ACCESS CONTROL OUT command 375
8.3.3.1 ACCESS CONTROL OUT introduction 375
8.3.3.2 MANAGE ACL service action 376
8.3.3.2.1 MANAGE ACL introduction 376
8.3.3.2.2 The Grant/Revoke ACE page 379
8.3.3.2.3 The Grant All ACE page 381
8.3.3.2.4 The Revoke Proxy Token ACE page 382
8.3.3.2.5 The Revoke All Proxy Tokens ACE page 382
8.3.3.3 DISABLE ACCESS CONTROLS service action 383
8.3.3.4 ACCESS ID ENROLL service action 383
8.3.3.5 CANCEL ENROLLMENT service action 385
8.3.3.6 CLEAR ACCESS CONTROLS LOG service action 385
8.3.3.7 MANAGE OVERRIDE LOCKOUT TIMER service action 386
8.3.3.8 OVERRIDE MGMT ID KEY service action 387
8.3.3.9 REVOKE PROXY TOKEN service action 388
8.3.3.10 REVOKE ALL PROXY TOKENS service action 389
8.3.3.11 ASSIGN PROXY LUN service action 389
8.3.3.12 RELEASE PROXY LUN service action 391
8.4 TARGET LOG PAGES well known logical unit 392

Annex A (informative) Terminology mapping 393

Annex B (Informative) PERSISTENT RESERVE IN/OUT functionality for RESERVE/RELEASE replacement 394
B.1 Introduction 394
B.2 Replacing the reserve/release method with the PERSISTENT RESERVE OUT COMMAND 394
B.3 Third party reservations 395

Annex C (Informative) Procedures for logging operations in SCSI 396
C.1 Procedures for logging operations in SCSI introduction 396

C.2 Logging operations terminology 396
C.3 LOG SENSE command 397
C.4 LOG SELECT command 400
C.5 Exception conditions during logging 403
C.5.1 Overview of exception conditions during logging 403
C.5.2 Pseudocode 1 405
C.5.3 Pseudocode 2 405
C.5.4 Pseudocode 3 405

Annex D (informative) Numeric order codes 406
D.1 Numeric order codes introduction 406
D.2 Additional sense codes 406
D.3 Operation codes 420
D.3.1 Operation codes 420
D.3.2 Additional operation codes for devices with the MCHNGR bit set to one 425
D.3.3 Additional operation codes for devices with the EncServ bit set to one 426
D.3.4 MAINTENANCE (IN) and MAINTENANCE (OUT) service actions 426
D.3.5 SERVICE ACTION IN and SERVICE ACTION OUT service actions 427
D.3.6 Variable length CDB service action codes 428
D.4 Diagnostic page codes 429
D.5 Log page codes 430
D.6 Mode page codes 431
D.7 VPD page codes 433
D.8 T10 IEEE binary identifiers 434

Annex E (informative) T10 vendor identification 435

Tables

Page

1 ISO and American numbering conventions examples 42
2 Binary power multiplier nomenclature 45
3 Typical CDB for 6-byte commands 47
4 Typical CDB for 10-byte commands 47
5 Typical CDB for 12-byte commands 48
6 Typical CDB for 16-byte commands 48
7 Typical CDB for long LBA 16-byte commands 49
8 Typical variable length CDB 49
9 Typical variable length CDB for long LBA 32-byte commands 50
11 Group Code values 51
10 OPERATION CODE byte 51
12 Sense data response codes 53
13 Descriptor format sense data 54
14 Sense data descriptor format 55
15 Sense data descriptor types 55
16 Information sense data descriptor format 55
17 Command-specific information sense data descriptor format 56
18 Sense key specific sense data descriptor format 57
19 Sense key specific field definitions 57
21 Actual retry count sense key specific data 58
20 Field pointer sense key specific data 58
22 Progress indication sense key specific data 59
23 Segment pointer sense key specific data 59
24 Field replaceable unit sense data descriptor format 60
25 Vendor specific sense data descriptor format 60
26 Fixed format sense data 61
27 Sense key descriptions 63
28 ASC and ASCQ assignments 64
29 Exception commands for background self-tests 81
30 Self-test mode summary 82
31 SPC commands that are allowed in the presence of various reservations 84
32 PERSISTENT RESERVE OUT service actions that are allowed in the presence of various reservations 86
33 Register behaviors for a REGISTER service action 90
34 Register behaviors for a REGISTER AND IGNORE EXISTING KEY service action 91
35 I_T Nexuses being registered 92
36 Register behaviors for a REGISTER AND MOVE service action 93
37 Processing for released persistent reservations 96
38 Preempting actions 98
39 Power Conditions 109
40 Types of MAM attributes 112
41 MAM attribute states 112
42 TIMESTAMP ORIGIN field 113
43 TIMESTAMP field format 113
44 Commands for all device types 114
45 CHANGE ALIASES command 116
46 CHANGE ALIASES parameter list 117
47 Alias entry format 118
48 Alias entry protocol identifiers 118
49 Protocol independent alias entry format codes 119
50 EXTENDED COPY command 120
51 EXTENDED COPY parameter list 121
52 EXTENDED COPY descriptor type codes 125
53 Target descriptor format 127
54 LU ID TYPE field 127
55 Device type specific parameters in target descriptors 128

56 Identification descriptor target descriptor format 129
57 Alias target descriptor format 130
58 Device type specific target descriptor parameters for block device types 130
59 Device type specific target descriptor parameters for sequential-access device types 131
60 Stream device transfer lengths 131
61 Device type specific target descriptor parameters for processor device types 132
62 Segment descriptor header 132
63 Descriptor Type Code Dependent Copy Manager Processing 134
64 PAD and CAT bit definitions 136
65 Block device to or from stream device segment descriptor 137
66 Block device to block device segment descriptor 139
67 Stream device to stream device segment descriptor 141
68 Inline data to stream device segment descriptor 142
69 Embedded data to stream device segment descriptor 144
70 Stream device to discard segment descriptor 145
71 Verify device operation segment descriptor 146
72 Block device with offset to or from stream device segment descriptor 147
73 Block device with offset to block device with offset segment descriptor 149
74 Write filemarks operation segment descriptor 150
75 Space operation segment descriptor 151
76 Locate operation segment descriptor 152
77 Tape device image copy segment descriptor 153
78 Register persistent reservation key segment descriptor 154
79 Third party persistent reservations source I_T nexus segment descriptor 155
80 INQUIRY command 157
81 Standard INQUIRY data format 158
82 Peripheral qualifier 159
83 Peripheral device type 159
84 Version 160
85 TPGS field 161
86 BQUE and CMDQUE bits definition 162
87 SPI-specific standard INQUIRY bits 162
88 Maximum logical device configuration table 163
89 CLOCKING field 163
90 LOG SELECT command 165
91 Page control (PC) field 165
92 LOG SENSE command 167
93 MODE SELECT(6) command 169
94 Mode page policies 169
95 MODE SELECT(10) command 171
96 MODE SENSE(6) command 171
97 Page control (PC) field 172
98 Mode page code usage for all devices 172
99 MODE SENSE(10) command 174
100 PERSISTENT RESERVE IN command 175
101 PERSISTENT RESERVE IN service action codes 175
102 PERSISTENT RESERVE IN parameter data for READ KEYS 176
103 PERSISTENT RESERVE IN parameter data for READ RESERVATION with no reservation held 177
104 PERSISTENT RESERVE IN parameter data for READ RESERVATION with reservation 177
105 Persistent reservation scope codes 178
106 Persistent reservation type codes 178
107 PERSISTENT RESERVE IN parameter data for REPORT CAPABILITIES 179
108 Persistent Reservation Type Mask format 180
109 PERSISTENT RESERVE IN parameter data for READ FULL STATUS 181
110 PERSISTENT RESERVE IN full status descriptor format 181
111 PERSISTENT RESERVE OUT command 183
112 PERSISTENT RESERVE OUT service action codes 184
113 PERSISTENT RESERVE OUT parameter list 185

114 PERSISTENT RESERVE OUT specify initiator ports additional parameter data 186
115 PERSISTENT RESERVE OUT service actions and valid parameters (part 1 of 2) 187
116 PERSISTENT RESERVE OUT command with REGISTER AND MOVE service action parameter list 188
117 PREVENT ALLOW MEDIUM REMOVAL command 190
118 PREVENT field 190
119 READ ATTRIBUTE command 191
120 READ ATTRIBUTE service action codes 192
121 READ ATTRIBUTE with ATTRIBUTE VALUES service action parameter list format 193
122 READ ATTRIBUTE with ATTRIBUTE LIST service action parameter list format 193
123 READ ATTRIBUTE with VOLUME LIST service action parameter list format 194
124 READ ATTRIBUTE with PARTITION LIST service action parameter list format 194
125 READ BUFFER command 195
126 READ BUFFER MODE field 195
127 READ BUFFER header 196
128 READ BUFFER descriptor 197
129 Buffer offset boundary 197
130 Echo buffer descriptor 198
131 READ MEDIA SERIAL NUMBER command 199
132 READ MEDIA SERIAL NUMBER parameter data format 199
133 RECEIVE COPY RESULTS command 200
134 RECEIVE COPY RESULTS service action codes 200
135 Parameter data for the COPY STATUS service action 201
136 COPY MANAGER STATUS field 202
137 COPY STATUS TRANSFER COUNT UNITS field 202
138 Parameter data for the RECEIVE DATA service action 203
139 Parameter data for the OPERATING PARAMETERS service action 204
140 Parameter data for the FAILED SEGMENT DETAILS service action 207
141 RECEIVE DIAGNOSTIC RESULTS command 208
142 REPORT ALIASES command 209
143 REPORT ALIASES parameter data 210
144 REPORT DEVICE IDENTIFIER command 211
145 REPORT DEVICE IDENTIFIER parameter data 211
146 REPORT LUNS command 212
147 SELECT REPORT field 212
148 REPORT LUNS parameter data format 213
149 REPORT PRIORITY command 214
150 PRIORITY REPORTED field 214
151 REPORT PRIORITY parameter data format 215
152 Priority descriptor format 215
153 REPORT SUPPORTED OPERATION CODES command 216
154 REPORT SUPPORTED OPERATION CODES reporting options 217
155 All_commands parameter data 218
156 Command descriptor format 218
157 One_command parameter data 219
158 SUPPORT values 219
159 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command 220
160 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS parameter data 220
161 REPORT TARGET PORT GROUPS command 222
162 REPORT TARGET PORT GROUPS parameter data format 222
163 Target port group descriptor format 223
164 ASYMMETRIC ACCESS STATE field 223
165 STATUS CODE field 224
166 Target port descriptor format 224
167 REPORT TIMESTAMP command 225
168 REPORT TIMESTAMP parameter data format 225
169 REQUEST SENSE command 226
170 SEND DIAGNOSTIC command 228
171 SELF-TEST CODE field 228

172 SET DEVICE IDENTIFIER command 230
173 SET DEVICE IDENTIFIER parameter list 231
174 SET PRIORITY command 231
175 I_T_L NEXUS TO SET field 232
176 SET PRIORITY parameter list format 232
177 SET TARGET PORT GROUPS command 233
178 SET TARGET PORT GROUPS parameter list format 234
179 Set target port group descriptor parameter list 235
180 ASYMMETRIC ACCESS STATE field 235
181 SET TIMESTAMP command 236
182 SET TIMESTAMP parameter data format 236
183 TEST UNIT READY command 237
184 Preferred TEST UNIT READY responses 237
185 WRITE ATTRIBUTE command 238
186 WRITE ATTRIBUTE parameter list format 239
187 WRITE BUFFER command 240
188 WRITE BUFFER MODE field 240
189 Application log data WRITE BUFFER format 245
190 ERROR TYPE field 245
191 CODE SET field 246
192 ERROR LOCATION FORMAT field 246
193 Diagnostic page format 247
194 Diagnostic page codes 247
195 Supported diagnostic pages 249
196 Log page format 250
197 Log parameter 250
198 Threshold met criteria 251
199 Log page codes 253
200 Application client log page 254
201 General usage application client parameter data 254
202 Parameter control bits for general usage parameters (0000h through 0FFFh) 255
203 Parameter code field for buffer over-run/under-run counters 255
204 Count basis definition 256
205 CAUSE field definition 256
206 Error counter log page codes 257
207 Parameter codes for error counter log pages 257
208 Informational Exceptions log page 257
209 Informational exceptions parameter codes 258
210 Informational exceptions general parameter data 258
211 Parameter control bits for Informational exceptions log parameter (0000h) 258
212 Non-medium error event parameter codes 259
213 Protocol Specific Port log page 260
214 Protocol specific port log parameter format 260
215 Self-Test Results log page 261
216 Self-test results log parameter format 261
217 Parameter control bits for self-test results log parameters 262
218 SELF-TEST RESULTS field 262
219 Start-Stop Cycle Counter log page 263
220 Parameter control bits for date of manufacture parameter (0001h) 264
221 Parameter control bits for accounting date parameter (0002h) 265
222 Parameter control bits for start-stop cycle counter parameters (0003h and 0004h) 265
224 Temperature log page 266
223 Supported log pages 266
225 Parameter control bits for temperature parameters (0000h and 0001h) 267
226 MAM ATTRIBUTE format 268
227 MAM attribute formats 268
228 MAM attribute identifier range assignments 269
229 Device type attributes 270

230 DEVICE VENDOR/SERIAL NUMBER attribute format 271
231 MEDIUM USAGE HISTORY attribute format 272
232 PARTITION USAGE HISTORY attribute format 274
233 Medium type attributes 276
234 MEDIUM TYPE and MEDIUM TYPE INFORMATION attributes 276
235 Host type attributes 277
236 TEXT LOCALIZATION IDENTIFIER attribute values 277
237 Mode parameter list 279
238 Mode parameter header(6) 279
239 Mode parameter header(10) 280
240 General mode parameter block descriptor 281
241 Page_0 mode page format 282
242 Sub_page mode page format 282
243 Mode page codes and subpage codes 283
244 Control mode page 284
245 Task set type (TST) field 284
246 QUEUE ALGORITHM MODIFIER field 285
247 Queue error management (QERR) field 285
248 Unit attention interlocks control (UA_INTLCK_CTRL) field 286
249 AUTOLOAD MODE field 287
250 Control Extension mode page 288
251 Disconnect-Reconnect mode page 289
252 Data transfer disconnect control 291
253 Extended mode page 291
254 Extended Device-Type Specific mode page 292
255 Informational Exceptions Control mode page 292
256 Method of reporting informational exceptions (MRIE) field 293
257 Power Condition mode page 295
258 Protocol Specific Logical Unit mode page 296
259 Page_0 format Protocol Specific Port mode page 297
260 Sub_page format Protocol Specific Port mode page 297
261 PROTOCOL IDENTIFIER values 299
262 Fibre Channel alias entry format codes 299
263 Fibre Channel world wide port name alias entry designation 300
264 Fibre Channel world wide port name with N_Port checking alias entry designation 300
265 RDMA alias entry format codes 301
266 RDMA target port identifier alias entry designation 301
267 InfiniBand global identifier with target port identifier checking alias entry designation 302
268 iSCSI alias entry format codes 302
269 iSCSI name alias entry designation 303
270 iSCSI name with binary IPv4 address alias entry designation 303
271 iSCSI name with IPname alias entry designation 304
272 iSCSI name with binary IPv6 address alias entry designation 305
273 Fibre Channel N_Port_Name EXTENDED COPY target descriptor format 306
274 Fibre Channel N_Port_ID EXTENDED COPY target descriptor format 307
275 Fibre Channel N_Port_ID with N_Port_Name checking target descriptor format 308
276 SCSI Parallel T_L EXTENDED COPY target descriptor format 309
277 IEEE 1394 EUI-64 EXTENDED COPY target descriptor format 310
278 RDMA EXTENDED COPY target descriptor format 311
279 iSCSI binary IPv4 address EXTENDED COPY target descriptor format 312
280 SAS serial SCSI protocol EXTENDED COPY target descriptor format 313
281 TransportID format 313
282 TransportID formats for specific SCSI transport protocols 314
283 Fibre Channel TransportID format 314
284 Parallel SCSI bus TransportID format 315
285 IEEE 1394 TransportID format 315
286 RDMA TransportID format 316
287 iSCSI TransportID formats 316

288 iSCSI initiator device TransportID format 316
289 iSCSI initiator port TransportID format 317
290 SAS Serial SCSI Protocol TransportID format 318
291 Vital product data page codes 319
292 ASCII Information VPD page 319
293 Device Identification VPD page 321
294 Identification descriptor 321
295 CODE SET field 322
296 ASSOCIATION field 322
297 IDENTIFIER TYPE field 322
298 Vendor specific IDENTIFIER field format 324
299 T10 vendor ID based IDENTIFIER field format 325
300 EUI-64 based identifier lengths 325
301 EUI-64 IDENTIFIER field format 326
302 EUI-64 based 12-byte IDENTIFIER field format 326
303 EUI-64 based 16-byte IDENTIFIER field format 327
304 NAA IDENTIFIER field format 327
305 Name Address Authority (NAA) field 327
306 NAA IEEE Extended IDENTIFIER field format 328
307 NAA IEEE Registered IDENTIFIER field format 328
308 NAA IEEE Registered Extended IDENTIFIER field format 329
309 Relative target port IDENTIFIER field format 329
310 RELATIVE TARGET PORT IDENTIFIER field 330
311 Target port group IDENTIFIER field format 330
312 Logical unit group IDENTIFIER field format 330
313 MD5 logical unit IDENTIFIER field format 331
314 MD5 logical unit identifier example available data 331
315 Example MD5 input for computation of a logical unit identifier 332
316 SCSI name string IDENTIFIER field format 332
317 Extended INQUIRY Data VPD page 333
318 Management Network Addresses VPD page 334
319 Network service descriptor format 335
320 Network services type 335
321 Mode Page Policy VPD page 336
322 Mode page policy descriptor 336
323 MODE PAGE POLICY field 337
324 SCSI Ports VPD page 337
325 SCSI port identification descriptor 338
326 RELATIVE PORT IDENTIFIER field 338
327 Target port descriptor 339
328 Software Interface Identification VPD page 340
329 Software interface identifier format 340
330 Supported VPD pages 341
331 Unit Serial Number VPD page 341
332 Well known logical unit numbers 342
333 Commands for the REPORT LUNS well known logical unit 342
334 Commands for the ACCESS CONTROLS well known logical unit 343
335 ACCESS CONTROL OUT management identifier key requirements 346
336 ACCESS CONTROL IN management identifier key requirements 346
337 Mandatory access controls resources 356
338 Optional access controls resources 357
339 Access Identifier types 357
340 AccessID access identifier format 357
341 ACCESS CONTROL IN service actions 358
342 ACCESS CONTROL IN command with REPORT ACL service action 358
343 ACCESS CONTROL IN with REPORT ACL parameter data format 359
344 ACL data page codes 360
345 Granted ACL data page format 360

346 Granted ACL data page LUACD descriptor format 361
347 Access mode values 361
348 Granted All ACL data page format 362
349 Proxy Tokens ACL data page format 362
350 Proxy token descriptor format 363
351 ACCESS CONTROL IN command with REPORT LU DESCRIPTORS service action 363
352 ACCESS CONTROL IN with REPORT LU DESCRIPTORS parameter data format 364
353 SUPPORTED LUN MASK FORMAT field format 365
354 Logical Unit descriptor format 366
355 ACCESS CONTROL IN command with REPORT ACCESS CONTROLS LOG service action 368
356 CDB LOG PORTION field values 368
357 ACCESS CONTROL IN with REPORT ACCESS CONTROLS LOG parameter data format 369
358 Parameter data LOG PORTION field values 369
359 Key Overrides access controls log portion page format 370
360 Invalid Keys access controls log portion page format 371
361 ACL LUN Conflicts access controls log portion page format 372
362 ACCESS CONTROL IN command with REPORT OVERRIDE LOCKOUT TIMER service action 373
363 ACCESS CONTROL IN with REPORT OVERRIDE LOCKOUT TIMER parameter data 373
364 ACCESS CONTROL IN command with REQUEST PROXY TOKEN service action 374
365 ACCESS CONTROL IN with REQUEST PROXY TOKEN parameter data 375
366 ACCESS CONTROL OUT service actions 375
367 ACCESS CONTROL OUT command format 376
368 ACCESS CONTROL OUT with MANAGE ACL parameter data format 377
369 ACE page codes 378
370 Grant/Revoke ACE page format 379
371 ACE page LUACD descriptor format 380
372 Access Coordinator Grant/Revoke ACE page actions 381
373 Grant All ACE page format 381
374 Revoke Proxy Token ACE page format 382
375 Revoke All Proxy Tokens ACE page format 382
376 ACCESS CONTROL OUT with DISABLE ACCESS CONTROLS parameter data format 383
377 ACCESS CONTROL OUT with ACCESS ID ENROLL parameter data format 384
378 ACCESS CONTROL OUT with CLEAR ACCESS CONTROLS LOG parameter data format 385
379 CLEAR ACCESS CONTROLS LOG LOG PORTION field values 386
380 ACCESS CONTROL OUT with MANAGE OVERRIDE LOCKOUT TIMER parameter data format 387
381 ACCESS CONTROL OUT with OVERRIDE MGMT ID KEY parameter data format 388
382 ACCESS CONTROL OUT with REVOKE PROXY TOKEN parameter data format 388
383 ACCESS CONTROL OUT with REVOKE ALL PROXY TOKENS parameter data format 389
384 ACCESS CONTROL OUT with ASSIGN PROXY LUN parameter data format 390
385 ACCESS CONTROL OUT with RELEASE PROXY LUN parameter data format 391
386 Commands for the TARGET LOG PAGES well known logical unit 392
A.1 SPC-3 to SPC-2 terminology mapping 393
B.1 PERSISTENT RESERVE OUT command features 394
C.1 LOG SENSE Command CDB fields 397
C.2 LOG SENSE returned parameter values 398
C.3 LOG SENSE save options 399
C.4 LOG SELECT CDB fields 400
C.5 LOG SELECT save options 401
C.6 LOG SELECT controller parameter values 402
C.7 Log parameter control byte saving definitions 403
C.9 Logging exception conditions 404
C.8 Log parameter control byte updating definitions 404
D.1 ASC and ASCQ assignments 406
D.2 Operation codes 420
D.3 Additional operation codes for devices with the MCHNGR bit set to one 425
D.4 Additional operation codes for devices with the EncServ bit set to one 426
D.5 MAINTENANCE (IN) and MAINTENANCE (OUT) service actions 426
D.6 SERVICE ACTION IN(12) and SERVICE ACTION OUT(12) service actions 427

D.7 SERVICE ACTION IN(16) and SERVICE ACTION OUT(16) service actions 427
D.8 Variable Length CDB Service Action Code Ranges 428
D.9 Variable Length CDB Service Action Codes Used by All Device Types 428
D.10 Diagnostic page codes 429
D.11 Log page codes 430
D.12 Mode page codes 431
D.13 VPD page codes 433
D.14 IEEE binary identifiers assigned by T10 434
E.1 T10 vendor identification list 435

Figures

Page
1 SCSI document relationships 24
2 Example state diagram 45
3 Device server interpretation of PREEMPT service action 99
4 Target port group example 104
5 Power condition state machine 110
6 ACL Structure 345