ISO/IEC 29341-16-10:2011-08 (E)

Information technology - UPnP Device Architecture - Part 16-10: Low Power Device Control Protocol - Low Power Proxy Service

Contents

Page

1 Overview and Scope....2
1.1 Referenced Specifications....2
1.1.1 Normative References....2
1.1.2 Informative References....2
1.2 Abbreviations....3
2 Service Modeling Definitions for Basic Power Management Proxy....3
2.1 ServiceType....3
2.2 State Variables....3
2.2.1 Derived data Types....3
2.2.2 A_ARG_TYPE_SearchCriteria....4
2.2.3 A_ARG_TYPE_PowerState....4
2.2.4 DeviceListInfo....5
2.2.5 A_ARG_TYPE_UUID....6
2.2.6 A_ARG_TYPE_Success....6
2.3 Eventing and Moderation....6
2.4 Actions....6
2.4.1 SearchSleepingDevices....6
2.4.2 WakeupDevice....7
2.5 Theory of Operation....8
2.5.1 Basic Power Management Proxy Control Point Behavior....8
2.5.2 Basic Power Management Proxy Service....9
3 XML Service Description....9
4 Test....11
Annex A (informative) Sample argument XML string....12

Table 1-1 — Abbreviations....3
Table 2-1 — State Variables for Basic Power Management Proxy Service....4
Table 2-2 — Values for A_ARG_TYPE_PowerState:....5
Table 2-3 — Event Moderation....6
Table 2-4 — Actions for BPMPX....6
Table 2-5 — Arguments for SearchSleepingDevices....7
Table 2-6 — Error Codes for SearchSleepingDevices....7
Table 2-7 — Arguments for WakeupDevice....8
Table 2-8 — Error Codes for WakeupDevice....8