

ISO/IEC 29341-16-11:2011-08 (E)

Information technology - UPnP Device Architecture - Part 16-11: Low Power Device Control Protocol - Low Power Service

Contents	Page
1 Overview and Scope.....	3
1.1 Referenced Specifications	4
1.2 Notation	4
1.3 Abbreviations	5
1.4 Non-goals	5
2 Service Modeling Definitions.....	5
2.1 ServiceType	5
2.2 State Variables.....	5
2.2.1 Derived data Types.....	5
2.2.2 BatteryLow	6
2.2.3 ExternalPowerSupplySource	7
2.2.4 WakeupMethod.....	7
2.2.5 PowerSupplyStatus.....	7
2.2.6 SleepPeriod.....	7
2.2.7 PowerState	8
2.2.8 Low power SSDP extensions.....	8
2.3 Eventing and Moderation	8
2.4 Generic LP-aware control point recommendations.....	8
2.5 Actions.....	9
2.5.1 GetPowerManagementInfo().....	9
2.5.2 Wakeup().....	10
2.5.3 GoToSleep()	11
2.6 Theory of Operation.....	11
2.6.1 Explanation of Actions and operations.....	11
2.6.2 Low power state behavior	12
3 XML Service Descriptions.....	14
4 Test	16
5 Sample Argument XML documents	16
5.1 PowerSupplyStatus	16
5.2 WakeUpMethod.....	16
Figure 1 — UPnP Low Power states.....	13

Table 1 — Low power states.....	3
Table 2 — Abbreviations.....	5
Table 3 — State Variables.....	6
Table 4 — SSDP power management extension headers.	8
Table 5 — State variable eventing.....	8
Table 6 — Actions.....	9
Table 7 — Arguments for GetPowerManagementInfo().....	9
Table 8 — Error Codes for GetPowerManagementInfo().....	10
Table 9 — Error Codes for WakeUp().....	10
Table 10 — Arguments for GoToSleep().....	11
Table 11 — Error Codes for GoToSleep().....	11
Table 12 — State machine Transition Description.....	14