

# ISO/IEC 29341-17-11:2011-08 (E)

## Information technology - UPnP Device Architecture - Part 17-11: Quality of Service Device Control Protocol - Level 3 - Quality of Service Manager Service

---

Contents	Page
1 Overview and Scope.....	3
1.1 References & Terms.....	3
1.1.1 References.....	3
1.1.2 Terms and Abbreviations.....	5
2 Service Modeling Definitions.....	12
2.1 ServiceType.....	12
2.2 State Variables.....	12
2.2.1 XML Fragments as UPnP Arguments.....	12
2.2.2 A_ARG_TYPE_TrafficDescriptor.....	13
2.2.3 A_ARG_TYPE_TrafficHandle.....	33
2.2.4 A_ARG_TYPE_NumTrafficDescriptors.....	33
2.2.5 A_ARG_TYPE_NumPolicyHolders.....	33
2.2.6 A_ARG_TYPE_ListOfTrafficDescriptors.....	33
2.2.7 A_ARG_TYPE_QmCapabilities.....	35
2.2.8 A_ARG_TYPE_ExtendedTrafficQosInfo.....	36
2.2.9 A_ARG_TYPE_ResultedQosType.....	38
2.2.10 Relationships Between State Variables.....	38
2.3 Eventing and Moderation.....	39
2.3.1 Event Model.....	39
2.4 Actions.....	39
2.4.1 RequestTrafficQos().....	39
2.4.2 UpdateTrafficQos().....	51
2.4.3 ReleaseTrafficQos().....	59
2.4.4 BrowseAllTrafficDescriptors().....	59
2.4.5 GetQmCapabilities().....	60
2.4.6 RequestExtendedTrafficQos().....	61
2.4.7 UpdateExtendedTrafficQos().....	66
2.4.8 Common Error Codes.....	70
2.5 Theory of Operation (Informative).....	72
2.5.1 Overview.....	72
2.5.2 Recovery from Failures.....	73
3 XML Service Description.....	75
4 Test.....	79
Annex A (normative) Traffic Descriptor Matrix.....	80
Annex B (informative) Methods for determining candidate streams for preemption based on UINs.....	83
Annex C (normative) The <i>res@tspec</i> property in the <i>ContentDirectory</i> Service.....	84
C.1 Definition of the XML Fragment.....	84

Figure 1 — An example traffic stream .....	22
Figure 2 — A traffic stream with a constant bit rate .....	24
Figure 3 — The non-constant bit-rate traffic (left) can be viewed as a constant bit-rate traffic of a higher constant bit-rate $D$ (right) .....	24
Table 1-1 — Abbreviations.....	5
Table 2-1 — State Variables .....	13
Table 2-2 — Meaning of <i>PolicyHolderConsultedType</i> parameter.....	18
Table 2-3 — Traffic Specification Parameters.....	21
Table 2-4 — Meaning of <i>RequestedQosType</i> parameter.....	22
Table 2-5 — Meaning of <i>ResultedQosType</i> parameter.....	38
Table 2-6 — Event Moderation.....	39
Table 2-7 — Actions .....	39
Table 2-8 — Arguments for <i>RequestTrafficQos()</i> .....	40
Table 2-9 — Elements that MUST equal those of the original TrafficDescriptor .....	42
Table 2-10 — Default Priorities used by the <i>QoS Manager</i> based on 802.1D (Annex G).....	44
Table 2-11 — Error Codes for <i>RequestTrafficQos()</i> .....	50
Table 2-12 — Elements that are allowed to be updated when calling <i>UpdateTrafficQos()</i> .....	52
Table 2-13 — Arguments for <i>UpdateTrafficQos()</i> .....	53
Table 2-14 — Error Codes for <i>UpdateTrafficQos</i> .....	58
Table 2-15 — Arguments for <i>ReleaseTrafficQos</i> .....	59
Table 2-16 — Error Codes for <i>ReleaseTrafficQos</i> .....	59
Table 2-17 — Arguments for <i>BrowseAllTrafficDescriptors</i> .....	60
Table 2-18 — Error Codes for <i>BrowseAllTrafficDescriptors</i> .....	60
Table 2-19 — Arguments for <i>GetQmCapabilities</i> .....	60
Table 2-20 — Error Codes for <i>GetQmCapabilities</i> .....	61
Table 2-21 — Arguments for <i>RequestExtendedTrafficQos</i> .....	61
Table 2-22 — Error Codes for <i>RequestExtendedTrafficQos</i> .....	65
Table 2-23 — Arguments for <i>UpdateExtendedTrafficQos</i> .....	66
Table 2-24 — Error Codes for <i>UpdateExtendedTrafficQos</i> .....	69
Table 2-25 — Common Error Codes .....	70