

# ISO/IEC 14165-243:2012-12 (E)

## Information technology - Fibre Channel - Part 243: Backbone 3 (FC-BB-3)

---

<b>Contents</b>	<b>Page</b>
FOREWORD .....	7
INTRODUCTION .....	8
1 Scope .....	9
2 Normative references .....	12
3 Terms, definitions and conventions .....	14
3.1 Terms and definitions .....	14
3.2 FC-BB-3_ATM definitions .....	17
3.3 FC-BB-3_SONET definitions .....	19
3.4 FC-BB-3_IP definitions .....	22
3.5 FC-BB-3_GFPT definitions .....	24
3.6 Editorial conventions .....	26
3.7 List of commonly used acronyms and abbreviations .....	27
3.7.1 General .....	27
3.7.2 FC-BB-3_ATM .....	28
3.7.3 FC-BB-3_SONET .....	28
3.7.4 FC-BB-3_IP .....	28
3.7.5 FC-BB-3_GFPT .....	28
3.8 Symbols .....	29
3.9 Keywords .....	29
4 FC-BB-3 structure and concepts .....	31
4.1 FC-BB-3 backbone mappings .....	31
4.2 FC-BB-3 reference models .....	31
4.3 FC-BB-3 models overview .....	33
4.3.1 FC-BB-3_ATM .....	33
4.3.2 FC-BB-3_SONET .....	34
4.3.3 FC-BB-3_IP .....	34
4.3.4 FC-BB-3_GFPT .....	34
4.4 FC-BB-3 requirements .....	35
4.4.1 Fibre Channel Class support .....	35
4.4.2 Payload transparency .....	35
4.4.3 Latency delay and timeout value .....	35
4.4.4 QoS and bandwidth .....	36
4.4.5 In-order delivery .....	36
4.4.6 Flow control .....	36
4.5 FC-BB-3 SW_ILS codes .....	36
5 FC-BB-3_ATM and FC-BB-3_SONET Messages and Formats .....	38
5.1 General .....	38
5.2 LLC/SNAP header format .....	38
5.3 BBW_Header format .....	38
5.4 BBW message payload format for SFC .....	39
5.5 BBW message payload format for SR .....	40
5.5.1 General .....	40
5.5.2 SR_Header formats .....	40
5.5.3 SR_BBW messages .....	41
5.5.4 Format field parameters .....	42
5.5.5 SR commands and responses .....	43
5.5.6 Exception condition reporting and recovery .....	47
6 SR and SFC Protocol Procedures .....	49
6.1 Applicability .....	49
6.2 SR protocol overview .....	49

6.3 Description of the SR procedure . . . . .	50
6.3.1 SR mode of operation . . . . .	50
6.3.2 SR procedure for addressing . . . . .	50
6.3.3 SR procedure for the use of the P/F bit . . . . .	50
6.3.4 SR procedure for data link set-up and disconnection . . . . .	50
6.3.5 Procedures for information transfer using multi-selective reject . . . . .	52
6.3.6 SR conditions for data link resetting or data link re-initialization . . . . .	56
6.3.7 SR procedures for data link resetting . . . . .	57
6.3.8 List of SR system parameters . . . . .	58
6.4 Simple Flow Control (SFC) . . . . .	59
7 FC-BB-3_ATM Structure and Concepts . . . . .	60
7.1 Applicability . . . . .	60
7.2 FC-BB-3_ATM overview . . . . .	60
7.3 FC-BB-3_ATM B_Access functional model . . . . .	61
7.3.1 Protocol layers . . . . .	61
7.3.2 B_Port FC interface . . . . .	61
7.3.3 ATM network interface . . . . .	61
7.3.4 FC-BB-3_ATM protocol interface . . . . .	62
7.3.5 B_Access Virtual ISL exchanges – Exchange B_Access Parameters (EBP) SW_ILS . . . . .	67
7.3.6 B_Access initialization state machine . . . . .	69
7.4 FC-BB-3_ATM network topologies . . . . .	72
7.5 Mapping and message encapsulation using AAL5 . . . . .	73
7.5.1 Overview . . . . .	73
7.5.2 Mapping BBW messages to AAL5 . . . . .	73
7.6 FC-BB-3_ATM service considerations . . . . .	76
7.6.1 ATM service type . . . . .	76
7.6.2 Latency delay and timeout value . . . . .	77
7.6.3 Bandwidth sharing and allocation . . . . .	77
7.6.4 Quality of Service (QoS) . . . . .	77
7.6.5 Delivery Order . . . . .	78
7.6.6 Loss and Flow Control . . . . .	78
8 FC-BB-3_SONET Structure and Concepts . . . . .	79
8.1 Applicability and related clauses . . . . .	79
8.2 FC-BB-3_SONET overview . . . . .	79
8.3 FC-BB-3_SONET functional model . . . . .	80
8.3.1 Fibre Channel network interface . . . . .	80
8.3.2 SONET network interface . . . . .	81
8.3.3 Mapping and encapsulation . . . . .	82
8.3.4 FC-BB-3_SONET forwarding . . . . .	82
8.3.5 Call handling . . . . .	82
8.3.6 Frame handling . . . . .	82
8.4 Mapping and Message encapsulation using HDLC-like framing . . . . .	82
8.4.1 Overview . . . . .	82
8.4.2 Mapping of BBW messages to HDLC format . . . . .	82
8.4.3 Mapping HDLC frames to SONET/SDH . . . . .	84
8.5 FC-BB-3_SONET service considerations . . . . .	87
8.5.1 Latency delay and timeout value . . . . .	87
8.5.2 Delivery order . . . . .	88
8.5.3 Loss and flow control . . . . .	88
9 FC-BB-3_IP Structure and Concepts . . . . .	89
9.1 Applicability . . . . .	89
9.2 FC-BB-3_IP overview . . . . .	89
9.3 VE_Port functional model . . . . .	90
9.3.1 FC-BB-3_IP interface protocol layers . . . . .	90
9.3.2 E_Port/F_Port FC interface . . . . .	90

9.3.3 FC Switching Element (SE) with FC routing . . . . .	90
9.3.4 FC-BB-3_IP protocol interface . . . . .	90
9.3.5 IP network interface . . . . .	96
9.4 B_Access functional model . . . . .	96
9.4.1 FC-BB-3_IP interface protocol layers . . . . .	96
9.4.2 B_Port FC interface . . . . .	96
9.4.3 FC-BB-3_IP protocol interface . . . . .	97
9.4.4 IP Network Interface . . . . .	102
9.5 FC-BB-3_IP Network Topologies . . . . .	102
9.6 Mapping and message encapsulation using TCP/IP . . . . .	103
9.6.1 Encapsulated frame structures . . . . .	103
9.6.2 TCP/IP encapsulation . . . . .	106
9.7 FC-BB-3_IP Protocol Procedures . . . . .	106
9.7.1 Overview . . . . .	106
9.7.2 Procedures for platform management . . . . .	106
9.7.3 Procedures for connection management . . . . .	108
9.7.4 Procedures for error detection recovery . . . . .	110
9.7.5 FC-BB-3_IP system parameters . . . . .	111
9.8 FC-BB-3_IP service considerations . . . . .	111
9.8.1 Latency delay . . . . .	111
9.8.2 Throughput . . . . .	111
9.8.3 Reliability . . . . .	112
9.8.4 Quality of Service (QoS) . . . . .	113
9.8.5 Delivery order . . . . .	113
9.8.6 IP multicast and broadcast . . . . .	114
9.8.7 Security and authentication . . . . .	114
10 FC-BB-3_GFPT Structure and Concepts . . . . .	115
10.1 Applicability . . . . .	115
10.2 FC-BB-3_GFPT overview . . . . .	115
10.3 FC-BB-3_GFPT functional model . . . . .	116
10.3.1 FC-BB-3_GFPT initialization . . . . .	116
10.3.2 FC-BB-3_GFPT initialization state machine . . . . .	116
10.3.3 Login Exchange Monitors . . . . .	120
10.3.4 Port initialization parameter observation and modification . . . . .	123
10.3.5 Handling of BB_SCs, BB_SCr, and R_RDY Primitive Signals and BB_Credit initialization . . . . .	123
10.3.6 FC-BB-3_GFPT flow control and WAN Primitive Signals . . . . .	124
10.3.7 Overview . . . . .	124
10.3.8 Adaptation of FC information for GFPT transport in FC-BB-3_GFPT . . . . .	126
10.3.9 WAN Holdoff Timeout Value (WAN_HOLDOFF_TOV) . . . . .	127
Annex A (normative) – Encoded SOF and EOF Ordered Sets . . . . .	128
Annex B (informative) –ATM Traffic Management and Signaling . . . . .	131
Annex C (informative) – SR Protocol Parameter Guidelines and State Diagram . . . . .	141
Annex D (informative) – FC-BB-3_GFPT interoperability guidelines and GFPT-specific interoperability guidelines . . . . .	144
BIBLIOGRAPHY . . . . .	145

Figure 1 – Scope and components of FC-BB-3_ATM/SONET models	10
Figure 2 – Scope and components of FC-BB-3_IP model	10
Figure 3 – Scope and components of FC-BB-3_GFPT model	11
Figure 4 – FC-BB-3_ATM reference model	32
Figure 5 – FC-BB-3_SONET reference model	32
Figure 6 – FC-BB-3_IP reference model	33
Figure 7 – FC-BB-3_GFPT reference model	33
Figure 8 – SR flow control protocol between two BBWs	49
Figure 9 – FC-BB-3_ATM network configuration	60
Figure 10 – FC-BB-3_ATM protocol layers	63
Figure 11 – FC-BB-3_ATM B_Access functional model	66
Figure 12 – FCATM_LEP and FCATM_DE	67
Figure 13 – Scope of B_Access Virtual ISL	67
Figure 14 – B_Access initialization state machine	70
Figure 15 – FC-BB-3_ATM network topologies	72
Figure 16 – AAL5 Mapping of a BBW message with SFC	75
Figure 17 – AAL5 Mapping of a BBW message with SR	76
Figure 18 – Recommended ATM bandwidth allocation for multiple VCs	77
Figure 19 – FC-BB-3_SONET network configuration	79
Figure 20 – FC-BB-3_SONET functional block diagram	81
Figure 21 – SONET SPE HDLC mapping example	85
Figure 22 – Path signal label: C2	85
Figure 23 – Encapsulation of BBW message into HDLC frame using SFC	86
Figure 24 – Encapsulation of BBW message into HDLC frame using SR	87
Figure 25 – FC-BB-3_IP network configuration	89
Figure 26 – FC-BB-3_IP VE_Port functional model	91
Figure 27 – FC-BB-3_IP Protocol Layers	92
Figure 28 – Scope of VE_Port Virtual ISL	94
Figure 29 – Security layers	95
Figure 30 – FC-BB-3_IP B_Access functional model	98
Figure 31 – Scope of B_Access Virtual ISL	99
Figure 32 – B_Access initialization state machine	101
Figure 33 – FC-BB-3_IP network topologies	103
Figure 34 – TCP/IP encapsulation of an encapsulated FC frame	106
Figure 35 – FC-BB-3_GFPT protocol levels and layers	115
Figure 36 – FC-BB-3_GFPT initialization state machine	117
Figure 37 – Example port initialization process	124
Figure B.1 – Cell Transfer Delay distribution	133
Figure B.2 – SVC signaling at the UNI and Switched payload	140
Figure C.1 – SR protocol state diagram	142

Table 1 – FC-BB-3 Organization	9
Table 2 – ISO and American Conventions	27
Table 3 – Models and resident FC_Port types	31
Table 4 – FC-BB-3 SW_ILS codes	37
Table 5 – FC-BB-3 ELS codes	37
Table 6 – BBW message structure	38
Table 7 – LLC/SNAP header	38
Table 8 – BBW_Header	38
Table 9 – Flow control protocol type encodings	39
Table 10 – BBW message payload structure for SFC	39
Table 11 – BBW message payload structure for SR	40
Table 12 – SR_Header format	40
Table 13 – SS bits encoding	41
Table 14 – MMMMM bit encoding	41
Table 15 – SR_BBW messages	42
Table 16 – SR_I message format	44
Table 17 – SR_SREJ payload format example	45
Table 18 – SR_FRMR payload format	47
Table 19 – EBP request payload	68
Table 20 – EBP accept payload	69
Table 21 – EBP reject reason code explanation	69
Table 22 – Mapping of BBW messages to AAL5 CPCS	74
Table 23 – ATM VBR-NRT service specification	78
Table 24 – SONET/SDH data rates	81
Table 25 – Mapping of BBW messages to HDLC format	83
Table 26 – FC-BB-3_SONET protocol ptack	85
Table 27 – EBP request payload	99
Table 28 – EBP accept payload	100
Table 29 – EBP reject reason code explanation	100
Table 30 – TCP/IP Segment structure carrying encapsulated FC frame	104
Table 31 – Encapsulated FC frame structure	104
Table 32 – TCP/IP Segment structure carrying encapsulated FSF	105
Table 33 – Encapsulated FSF structure	105
Table 34 – ASF request payload	108
Table 35 – ASF accept response payload	108
Table 36 – FC-BB-3_GFPT initialization state machine keywords	116
Table 37 – Login Exchange Monitor (LEM) state machine	122
Table 38 – Values of FC-BB-3_GFPT ASFC_PAUSE and ASFC_RESUME Primitive Signals	125
Table 39 – Values of FC-BB-3_GFPT PING and PING_ACK Primitive Signals.	126
Table A.1 – Byte-encoded Frame delimiter format	128
Table A.3 – FC-BB-3 SOF Codes	129
Table A.2 – DS-Code Definition	129
Table A.4 – FC-BB-3 EOF Codes	130
Table B.1 – I.356 defined QoS parameters for different Traffic Classes	134
Table B.2 – Service Categories and its Traffic and QoS Attributes	136
Table B.3 – ATM service categories and guarantees	138