# ISO/IEC 29145-1:2014-03 (E)

## Information technology - Wireless Beacon-enabled Energy Efficient Mesh network (WiBEEM) for wireless home netwo rk services - Part 1: PHY Layer

## Contents

Page


FOREWORD ..... 5
INTRODUCTION ..... 7
1 Scope ..... 8
2 Normative reference ..... 8
3 Terms, definitions and abbreviations ..... 8
3.1 Terms and definitions ..... 8
3.2 Abbreviations ..... 10
3.3 Conventions ..... 11
4 Conformance ..... 11
5 Overview of the WiBEEM technology ..... 12
5.1 General description ..... 12
5.2 Functions and descriptions of device types ..... 13
5.3 Functional overview of WiBEEM ..... 13
5.3.1 General ..... 13
5.3.2 Superframe structure of WiBEEM ..... 13
5.3.3 Data transfer model ..... 14
6 PHY layer specifications ..... 15
6.1 General ..... 15
6.2 General requirements and definitions ..... 16
6.2.1 General ..... 16
6.2.2 Operating frequency range ..... 16
6.2.3 Channel assignments and numbering ..... 16
6.2.4 RF power measurement ..... 16
6.2.5 Transmit power ..... 17
6.2.6 Out-of-band spurious emission ..... 17
6.2.7 Receiver sensitivity definitions ..... 17
6.3 PHY service specifications ..... 17
6.3.1 General ..... 17
6.3.2 PHY data service ..... 18
6.3.3 PHY management service ..... 20
6.3.4 PHY enumerations description ..... 27
6.4 PPDU format ..... 28
6.4.1 Function ..... 28
6.4.2 General packet format ..... 28
6.5 PHY constants and PIB attributes ..... 29
6.5.1 Function ..... 29
6.5.2 PHY constants ..... 30
6.5.3 PHY PIB attributes ..... 30

6.6 2 450 MHz PHY specifications ..... 30
6.6.1 Requirements ..... 30
6.6.2 Data rate ..... 30
6.6.3 Modulation and spreading ..... 31
6.7 General radio specifications ..... 34
6.7.1 Application of specifications ..... 34
6.7.2 TX-to-RX turnaround time ..... 34
6.7.3 RX-to-TX turnaround time ..... 34
6.7.4 Error-vector magnitude (EVM) definition ..... 34
6.7.5 Transmit centre frequency tolerance ..... 35
6.7.6 Transmit power ..... 35
6.7.7 Receiver maximum input level of desired signal ..... 35
6.7.8 Receiver ED ..... 35
6.7.9 LQI ..... 35
6.7.10 CCA ..... 36
Bibliography ..... 37

Figure 1 – Superframe structure of WiBEEM ..... 13
Figure 2 – Communication from an end device to a co-ordinator in a beacon and non-beacon mode ..... 14
Figure 3 – Communication from a co-ordinator to an end device in a beacon and non-beacon mode ..... 14
Figure 4 – Communications between co-ordinators in a beacon and non-beacon mode ..... 15
Figure 5 – Communications between end devices ..... 15
Figure 6 – PHY reference model ..... 17
Figure 7 – Modulation and spreading functions ..... 31
Figure 8 – Symbol-to-chip mapping ..... 32
Figure 9 – O-QPSK chip offset ..... 32
Figure 10 – Sample baseband chip sequences with pulse shaping ..... 33
Figure 11 – Error vector calculation ..... 34

Table 1 – Frequency bands and data rate ..... 16
Table 2 – Receiver sensitivity definitions ..... 17
Table 3 – PD-SAP primitives ..... 18
Table 4 – PD_Data.request parameters ..... 18
Table 5 – PD_DATA.confirm parameters ..... 19
Table 6 – PD_DATA.indication parameters ..... 20
Table 7 – PLME-SAP primitives ..... 20
Table 8 – PLME-CCA confirm primitive ..... 21
Table 9 – PLME_ED.confirm parameters ..... 22
Table 10 – PLME_GET.request parameters ..... 23
Table 11 – PLME_GET.confirm parameters ..... 24
Table 12 – PLME-SET-TRX-STATE.request parameters ..... 24
Table 13 – PLME-SET-TRX-STATE.confirm parameters ..... 25

Table 14 – PLME_SET.request parameters ..... 26
Table 15 – PLME_SET.confirm parameters ..... 27
Table 16 – PHY enumerations description ..... 28
Table 17 – Format of the PDU ..... 28
Table 18 – Format of the SFD field ..... 29
Table 19 – Frame length values ..... 29
Table 20 – PHY constants ..... 30
Table 21 – PHY PIB attributes ..... 30
Table 22 – Minimum receiver jamming resistance requirements for 2 450 MHz PHY ..... 33