

ISO/IEC 29145-1:2014-03 (E)

Information technology - Wireless Beacon-enabled Energy Efficient Mesh network (WiBEEM) for wireless home network services - Part 1: PHY Layer

Contents	Page
FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative reference.....	8
3 Terms, definitions and abbreviations.....	8
3.1 Terms and definitions.....	8
3.2 Abbreviations.....	10
3.3 Conventions.....	11
4 Conformance.....	11
5 Overview of the WiBEEM technology.....	12
5.1 General description.....	12
5.2 Functions and descriptions of device types.....	13
5.3 Functional overview of WiBEEM.....	13
5.3.1 General.....	13
5.3.2 Superframe structure of WiBEEM.....	13
5.3.3 Data transfer model.....	14
6 PHY layer specifications.....	15
6.1 General.....	15
6.2 General requirements and definitions.....	16
6.2.1 General.....	16
6.2.2 Operating frequency range.....	16
6.2.3 Channel assignments and numbering.....	16
6.2.4 RF power measurement.....	16
6.2.5 Transmit power.....	17
6.2.6 Out-of-band spurious emission.....	17
6.2.7 Receiver sensitivity definitions.....	17
6.3 PHY service specifications.....	17
6.3.1 General.....	17
6.3.2 PHY data service.....	18
6.3.3 PHY management service.....	20
6.3.4 PHY enumerations description.....	27
6.4 PPDU format.....	28
6.4.1 Function.....	28
6.4.2 General packet format.....	28
6.5 PHY constants and PIB attributes.....	29
6.5.1 Function.....	29
6.5.2 PHY constants.....	30
6.5.3 PHY PIB attributes.....	30

6.6	2 450 MHz PHY specifications	30
6.6.1	Requirements	30
6.6.2	Data rate	30
6.6.3	Modulation and spreading.....	31
6.7	General radio specifications	34
6.7.1	Application of specifications.....	34
6.7.2	TX-to-RX turnaround time	34
6.7.3	RX-to-TX turnaround time	34
6.7.4	Error-vector magnitude (EVM) definition	34
6.7.5	Transmit centre frequency tolerance	35
6.7.6	Transmit power	35
6.7.7	Receiver maximum input level of desired signal.....	35
6.7.8	Receiver ED	35
6.7.9	LQI	35
6.7.10	CCA.....	36
	Bibliography.....	37
	Figure 1 – Superframe structure of WiBEEM	13
	Figure 2 – Communication from an end device to a co-ordinator in a beacon and non-beacon mode	14
	Figure 3 – Communication from a co-ordinator to an end device in a beacon and non-beacon mode	14
	Figure 4 – Communications between co-ordinators in a beacon and non-beacon mode	15
	Figure 5 – Communications between end devices	15
	Figure 6 – PHY reference model	17
	Figure 7 – Modulation and spreading functions	31
	Figure 8 – Symbol-to-chip mapping.....	32
	Figure 9 – O-QPSK chip offset.....	32
	Figure 10 – Sample baseband chip sequences with pulse shaping.....	33
	Figure 11 – Error vector calculation	34
	Table 1 – Frequency bands and data rate	16
	Table 2 – Receiver sensitivity definitions	17
	Table 3 – PD-SAP primitives.....	18
	Table 4 – PD_Data.request parameters	18
	Table 5 – PD_DATA.confirm parameters.....	19
	Table 6 – PD_DATA.indication parameters	20
	Table 7 – PLME-SAP primitives	20
	Table 8 – PLME-CCA confirm primitive	21
	Table 9 – PLME_ED.confirm parameters	22
	Table 10 – PLME_GET.request parameters	23
	Table 11 – PLME_GET.confirm parameters	24
	Table 12 – PLME-SET-TRX-STATE.request parameters	24
	Table 13 – PLME-SET-TRX-STATE.confirm parameters	25

Table 14 – PLME_SET.request parameters	26
Table 15 – PLME_SET.confirm parameters.....	27
Table 16 – PHY enumerations description	28
Table 17 – Format of the PDU	28
Table 18 – Format of the SFD field	29
Table 19 – Frame length values	29
Table 20 – PHY constants.....	30
Table 21 – PHY PIB attributes	30
Table 22 – Minimum receiver jamming resistance requirements for 2 450 MHz PHY	33