

ISO/IEC 29145-3:2014-03 (E)

Information technology - Wireless Beacon-enabled Energy Efficient Mesh network (WiBEEM) for wireless home network services - Part 3: NWK Layer

| Contents | Page |
|---|------|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 5 |
| 1 Scope..... | 6 |
| 2 Normative references..... | 6 |
| 3 Terms, definitions and abbreviations..... | 6 |
| 3.1 Terms and definitions..... | 6 |
| 3.2 Abbreviations..... | 7 |
| 3.3 Conventions..... | 8 |
| 4 Conformance..... | 8 |
| 5 Overview of the WiBEEM technology..... | 8 |
| 6 NWK layer specifications..... | 8 |
| 6.1 General..... | 8 |
| 6.2 NWK layer service specifications..... | 8 |
| 6.2.1 Overview..... | 8 |
| 6.2.2 NWK data service..... | 9 |
| 6.2.3 NWK management service..... | 12 |
| 6.2.4 Network formation..... | 14 |
| 6.2.5 Allowing devices to join..... | 16 |
| 6.2.6 Begin as a router..... | 18 |
| 6.2.7 Joining a network..... | 19 |
| 6.2.8 Joining a device directly to a network..... | 22 |
| 6.2.9 Leaving a network..... | 24 |
| 6.2.10 Resetting a device..... | 26 |
| 6.2.11 Receiver synchronisation..... | 27 |
| 6.2.12 Information base maintenance..... | 30 |
| Bibliography..... | 34 |
| Figure 1 – NWK layer structure..... | 9 |
| Figure 2 – Message sequence chart for resetting the network layer..... | 27 |
| Figure 3 – Message sequence chart for synchronising in a non-beaconing network..... | 30 |
| Table 1 – NLDE-DATA.request parameters..... | 10 |
| Table 2 – NLDE-DATA.confirm parameters..... | 11 |
| Table 3 – NLDE-DATA.indication parameters..... | 12 |
| Table 4 – Summary of primitives used by NWK layer..... | 12 |
| Table 5 – NLME-NETWORK-DISCOVERY.request parameters..... | 13 |
| Table 6 – NLME-WiBEEM-DISCOVERY.confirm paramaters..... | 14 |
| Table 7 – Network descriptor information fields..... | 14 |
| Table 8 – NLME-WRC-OPERATING.request parameters..... | 15 |
| Table 9 – NLME-NETWORK-FORMATION.confirm parameters..... | 16 |
| Table 10 – NLME-ALLOW-JOINING.request..... | 17 |
| Table 11 – NLME-ALLOW-JOINING.confirm parameters..... | 17 |

| | |
|--|----|
| Table 12 – NLME-SET-SUPERFRAME.request parameters | 18 |
| Table 13 – NLME-SET-SUPERFRAME.confirm parameters | 19 |
| Table 14 – NLME-JOIN.request parameters | 20 |
| Table 15 – NLME-JOIN.indication parameters | 21 |
| Table 16 – NLME-JOIN.confirm parameters | 22 |
| Table 17 – NLME-DETERMINED-JOIN.request parameters | 22 |
| Table 18 – Capability information parameter format | 23 |
| Table 19 – NLME-DETERMINED-JOIN.confirm parameters | 23 |
| Table 20 – NLME-LEAVE.request parameters | 24 |
| Table 21 – NLME-LEAVE.indication parameters | 25 |
| Table 22 – NLME-LEAVE.confirm parameters | 25 |
| Table 23 – NLME-RESET.confirm parameters | 27 |
| Table 24 – NLME-SYNC.request parameters | 28 |
| Table 25 – NLME-SYNC.confirm parameters | 29 |
| Table 26 – NLME-READ-NIB.request parameters | 30 |
| Table 27 – NLME-READ-NIB.confirm parameters | 31 |
| Table 28 – NLME-WRITE-NIB.request parameters | 32 |
| Table 29 – NLME-WRITE-NIB.confirm parameters | 33 |