ISO/IEC 14763-3:2014-06 (E)

Information technology - Implementation and operation of customer premises cabling - Part 3: Testing of optical fibre cabling

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
2 Normative references 9
3 Terms, definitions and abbreviations 10
3.1 Terms and definitions 10
3.2 Abbreviations 13
3.3 Symbols 13
4 Conformance 14
5 General requirements 14
5.1 Test system 14
5.2 Reference measurement and calibration 15
5.3 Environmental conditions 15
5.3.1 Protection of transmission and terminal equipment 15
5.3.2 Inspecting and cleaning connectors 15
5.3.3 Use of test equipment 15
5.3.4 Relevance of measurement 16
5.3.5 Treatment of marginal test results 16
5.4 Documentation 16
6 Test equipment 16
6.1 Light source and power meter 16
6.1.1 General 16
6.1.2 Light sources 16
6.1.3 Power meters 17
6.1.4 Test system stability (ffs) 17
6.2 OTDR 17
6.2.1 General 17
6.2.2 OTDR characterization using a launch test cord and a tail test cord 18
6.3 Test cords and adapters 18
6.3.1 Connecting hardware at test interfaces 18
6.3.2 Reference connector requirements 19
6.3.3 Test cords 20
6.4 MMF launched modal distribution 22
6.5 SMF launch condition 22
7 Inspection equipment 22
8 Cabling under test – Channels and permanent links 23
8.1 General 23
8.2 Reference planes 23
8.3 Wavelength of measurement 24
8.4 Direction of measurement 24

9 Testing of installed cabling 25
9.1 Attenuation 25
9.1.1 LSPM 25
9.1.2 OTDR 29
9.2 Propagation delay 31
9.2.1 Test method 31
9.2.2 Treatment of results 32
9.3 Length 32
9.3.1 Test method 32
9.3.2 Measurement uncertainty 32
9.3.3 Treatment of results 32
10 Testing of cabling components within installed cabling 33
10.1 Attenuation of optical fibre cable 33
10.1.1 Test method 33
10.1.2 Measurement uncertainty 33
10.1.3 Treatment of results 33
10.2 Attenuation of local and remote test interfaces 34
10.2.1 Test method 34
10.2.2 Test system measurement uncertainty 34
10.2.3 Treatment of results 35
10.3 Attenuation of connecting hardware 36
10.3.1 Test method 36
10.3.2 Treatment of results 36
10.4 Return loss of connecting hardware 37
10.4.1 Test method (in accordance with IEC 61300-3-6, method 2) 37
10.4.2 Treatment of results 38
10.4.3 Measurement uncertainty 39
10.5 Optical fibre length 39
10.5.1 Test method 39
10.5.2 Measurement uncertainty 41
10.5.3 Treatment of results 41
10.6 Attenuation of cords 41
10.6.1 Test method 41
10.6.2 Treatment of results 42
11 Inspection of cabling and cabling components 42
11.1 Optical fibre continuity 42
11.2 Cabling polarity 42
11.3 Optical fibre cable length 42
11.4 Inspection of optical fibre end faces 43
11.5 Optical fibre core size 43

Annex A (normative) Launch modal conditions for testing multimode optical fibre cabling 44
Annex B (normative) Visual inspection criteria for connectors 45
Annex C (informative) Optical time domain reflectometry 46
C.1 Operational capability 46
C.1.1 Effective characterization 46
C.1.2 Dynamic range 46
C.1.3 Pulse width 46
C.1.4 Integration or sample count 46
C.2 Limitations of OTDR capability 47
C.2.1 Minimum lengths of operation – Attenuation dead zone 47
C.2.2 Ghosting 48
C.2.3 Effective group index of refraction 49
C.2.4 Backscattering coefficient 49
Annex D (normative) Inspection and testing of test and substitution test cords 50
D.1 General requirements 50
D.2 Attenuation (test and substitution test cord reference connections) 50
Annex E (informative) Enhanced three-test-cord and one-test-cord reference methods for link and channel attenuation 52
E.1 Reference methods for link attenuation 52
E.2 One-test-cord reference method for link attenuation 52
E.3 Test method for channel attenuation 52
Annex F (informative) Quality planning 53
F.1 Inspection and test schedules 53
F.2 Stage 1 inspection and testing 53
F.3 Stage 2 testing 53
F.3.1 Basic test group 53
F.3.2 Extended test group 54
Annex G (informative) Examples of calculations of channel and permanent link limits 55
G.1 Channel measurement 55
G.2 Permanent link measurement 55
Annex H (informative) Cleaning and inspection of fibre optic connections 57
Bibliography 58

Figure 1 – Relationship of related International Standards 8
Figure 2 – Test system and the cabling under test 15
Figure 3 – OTDR characterization using a launch test cord and a tail test cord 18
Figure 4 – An example of test cord labelling and identification 20
Figure 5 – OTDR launch test cord and/or tail test cord schematic 21
Figure 6 – Channels and permanent links in accordance with ISO/IEC 11801 and equivalent standards 23
Figure 7 – Channel and permanent link test configuration 24
Figure 8 – LSPM enhanced three-test-cord attenuation measurement of installed channels 26
Figure 9 – LSPM one test cord attenuation measurement of installed permanent links 27
Figure 10 – OTDR measurement of installed cabling (channel): 2 point attenuation measurement method 30
Figure 11 – OTDR measurement of installed cabling (permanent link) 31
Figure 12 – OTDR measurement of optical fibre attenuation 34
Figure 13 – OTDR measurement of connection attenuation 35
Figure 14 – OTDR measurement of joint attenuation 37
Figure 15 – OTDR measurement of return loss 38
Figure 16 – Determination of length using an OTDR 39
Figure 17 – OTDR characterization of a SMF permanent link containing a break 40
Figure 18 – OTDR characterization of a permanent link containing a macrobend 41
Figure 19 – Measurement of cord interface attenuation 42
Figure C.1 – OTDR characterization using different length launch test cords 47
Figure C.2 – OTDR characterization showing ghost effects 48
Figure C.3 – OTDR characterization showing complex ghost effects 49
Figure D.1 – Measurement of substitution test cord interface attenuation 50

Table 1 – MMF light source characteristics 17
Table 2 – SMF light source characteristics 17
Table 3 – Non-LC reference connector requirements 19
Table 4 – Connecting hardware attenuation 28
Table C.1 – Default effective group IOR values 49
Table C.2 – Default backscattering coefficient values 49