

# ISO/IEC 14763-3:2014-06 (E)

## Information technology - Implementation and operation of customer premises cabling - Part 3: Testing of optical fibre cabling

---

### CONTENTS

- FOREWORD ..... 6
- INTRODUCTION ..... 8
- 1 Scope ..... 9
- 2 Normative references ..... 9
- 3 Terms, definitions and abbreviations ..... 10
  - 3.1 Terms and definitions ..... 10
  - 3.2 Abbreviations ..... 13
  - 3.3 Symbols ..... 13
- 4 Conformance ..... 14
- 5 General requirements ..... 14
  - 5.1 Test system ..... 14
  - 5.2 Reference measurement and calibration ..... 15
  - 5.3 Environmental conditions ..... 15
    - 5.3.1 Protection of transmission and terminal equipment ..... 15
    - 5.3.2 Inspecting and cleaning connectors ..... 15
    - 5.3.3 Use of test equipment ..... 15
    - 5.3.4 Relevance of measurement ..... 16
    - 5.3.5 Treatment of marginal test results ..... 16
  - 5.4 Documentation ..... 16
- 6 Test equipment ..... 16
  - 6.1 Light source and power meter ..... 16
    - 6.1.1 General ..... 16
    - 6.1.2 Light sources ..... 16
    - 6.1.3 Power meters ..... 17
    - 6.1.4 Test system stability (ffs) ..... 17
  - 6.2 OTDR ..... 17
    - 6.2.1 General ..... 17
    - 6.2.2 OTDR characterization using a launch test cord and a tail test cord ..... 18
  - 6.3 Test cords and adapters ..... 18
    - 6.3.1 Connecting hardware at test interfaces ..... 18
    - 6.3.2 Reference connector requirements ..... 19
    - 6.3.3 Test cords ..... 20
  - 6.4 MMF launched modal distribution ..... 22
  - 6.5 SMF launch condition ..... 22
- 7 Inspection equipment ..... 22
- 8 Cabling under test – Channels and permanent links ..... 23
  - 8.1 General ..... 23
  - 8.2 Reference planes ..... 23
  - 8.3 Wavelength of measurement ..... 24
  - 8.4 Direction of measurement ..... 24

9	Testing of installed cabling .....	25
9.1	Attenuation .....	25
9.1.1	LSPM .....	25
9.1.2	OTDR .....	29
9.2	Propagation delay .....	31
9.2.1	Test method .....	31
9.2.2	Treatment of results.....	32
9.3	Length .....	32
9.3.1	Test method .....	32
9.3.2	Measurement uncertainty.....	32
9.3.3	Treatment of results.....	32
10	Testing of cabling components within installed cabling .....	33
10.1	Attenuation of optical fibre cable .....	33
10.1.1	Test method .....	33
10.1.2	Measurement uncertainty.....	33
10.1.3	Treatment of results.....	33
10.2	Attenuation of local and remote test interfaces.....	34
10.2.1	Test method .....	34
10.2.2	Test system measurement uncertainty.....	34
10.2.3	Treatment of results.....	35
10.3	Attenuation of connecting hardware .....	36
10.3.1	Test method .....	36
10.3.2	Treatment of results.....	36
10.4	Return loss of connecting hardware .....	37
10.4.1	Test method (in accordance with IEC 61300-3-6, method 2) .....	37
10.4.2	Treatment of results.....	38
10.4.3	Measurement uncertainty.....	39
10.5	Optical fibre length.....	39
10.5.1	Test method .....	39
10.5.2	Measurement uncertainty.....	41
10.5.3	Treatment of results.....	41
10.6	Attenuation of cords .....	41
10.6.1	Test method .....	41
10.6.2	Treatment of results.....	42
11	Inspection of cabling and cabling components .....	42
11.1	Optical fibre continuity .....	42
11.2	Cabling polarity.....	42
11.3	Optical fibre cable length .....	42
11.4	Inspection of optical fibre end faces .....	43
11.5	Optical fibre core size .....	43

Annex A (normative) Launch modal conditions for testing multimode optical fibre cabling.....	44
Annex B (normative) Visual inspection criteria for connectors .....	45
Annex C (informative) Optical time domain reflectometry .....	46
C.1 Operational capability .....	46
C.1.1 Effective characterization.....	46
C.1.2 Dynamic range .....	46
C.1.3 Pulse width.....	46
C.1.4 Integration or sample count .....	46
C.2 Limitations of OTDR capability .....	47
C.2.1 Minimum lengths of operation – Attenuation dead zone .....	47
C.2.2 Ghosting.....	48
C.2.3 Effective group index of refraction .....	49
C.2.4 Backscattering coefficient .....	49
Annex D (normative) Inspection and testing of test and substitution test cords.....	50
D.1 General requirements .....	50
D.2 Attenuation (test and substitution test cord reference connections) .....	50
Annex E (informative) Enhanced three-test-cord and one-test-cord reference methods for link and channel attenuation .....	52
E.1 Reference methods for link attenuation .....	52
E.2 One-test-cord reference method for link attenuation.....	52
E.3 Test method for channel attenuation .....	52
Annex F (informative) Quality planning .....	53
F.1 Inspection and test schedules .....	53
F.2 Stage 1 inspection and testing .....	53
F.3 Stage 2 testing.....	53
F.3.1 Basic test group.....	53
F.3.2 Extended test group.....	54
Annex G (informative) Examples of calculations of channel and permanent link limits .....	55
G.1 Channel measurement .....	55
G.2 Permanent link measurement.....	55
Annex H (informative) Cleaning and inspection of fibre optic connections .....	57
Bibliography.....	58

Figure 1 – Relationship of related International Standards .....	8
Figure 2 – Test system and the cabling under test .....	15
Figure 3 – OTDR characterization using a launch test cord and a tail test cord .....	18
Figure 4 – An example of test cord labelling and identification .....	20
Figure 5 – OTDR launch test cord and/or tail test cord schematic .....	21
Figure 6 – Channels and permanent links in accordance with ISO/IEC 11801 and equivalent standards.....	23
Figure 7 – Channel and permanent link test configuration .....	24
Figure 8 – LSPM enhanced three-test-cord attenuation measurement of installed channels .....	26
Figure 9 – LSPM one test cord attenuation measurement of installed permanent links .....	27
Figure 10 – OTDR measurement of installed cabling (channel): 2 point attenuation measurement method .....	30
Figure 11 – OTDR measurement of installed cabling (permanent link) .....	31
Figure 12 – OTDR measurement of optical fibre attenuation .....	34
Figure 13 – OTDR measurement of connection attenuation.....	35
Figure 14 – OTDR measurement of joint attenuation.....	37
Figure 15 – OTDR measurement of return loss .....	38
Figure 16 – Determination of length using an OTDR .....	39
Figure 17 – OTDR characterization of a SMF permanent link containing a break .....	40
Figure 18 – OTDR characterization of a permanent link containing a macrobend .....	41
Figure 19 – Measurement of cord interface attenuation.....	42
Figure C.1 – OTDR characterization using different length launch test cords .....	47
Figure C.2 – OTDR characterization showing ghost effects .....	48
Figure C.3 – OTDR characterization showing complex ghost effects.....	49
Figure D.1 – Measurement of substitution test cord interface attenuation.....	50
Table 1 – MMF light source characteristics .....	17
Table 2 – SMF light source characteristics.....	17
Table 3 – Non-LC reference connector requirements .....	19
Table 4 – Connecting hardware attenuation .....	28
Table C.1 – Default effective group IOR values.....	49
Table C.2 – Default backscattering coefficient values .....	49