ISO/IEC 29341-12-11:2015-06 (E)

Information technology - UPnP Device Architecture - Part 12-11: Remote User Interface Device Control Protocol - Remote User Interface Server Service

Contents

Page

Foreword iv

Introduction v

1. Scope 1

2. Normative References 1

3. Service Modeling Definitions 2
3.1. ServiceType 2
3.2. State Variables 2
3.2.1. UIListingUpdate 2
3.2.2. A_ARG_TYPE_DeviceProfile 2
3.2.3. A_ARG_TYPE_URI 3
3.2.4. A_ARG_TYPE_CompatibleUIs 3
3.2.5. A_ARG_TYPE_String 3
3.2.6. A_ARG_TYPE_Int 3
3.3. Eventing and Moderation 3
3.4. Actions 4
3.4.1. GetCompatibleUIs 4
3.4.2. SetUILifetime 5
3.4.3. Non-Standard Actions Implemented by a UPnP Vendor 6
3.4.4. Relationships Between Actions 6
3.4.5. Common Error Codes 6

4. Theory of Operation 7
4.1. Example Values of State Variables 7
4.1.1. A_ARG_TYPE_URI 7
4.1.2. A_ARG_TYPE_CompatibleUIs 7
4.1.3. A_ARG_TYPE_DeviceProfile 11
4.1.4. UIListingUpdate 12
4.1.5. UIFilter Examples 12

5. A_ARG_TYPE_CompatibleUIs XSD Schema 14

6. DeviceProfile XSD Schema 15

7. XML Service Description 16

LIST OF TABLES Table 1: Service State Variables 2

Table 2: Event moderation 3

Table 3: Actions 4

Table 4: Arguments for GetCompatibleUIs() 4

Table 5: Arguments for SetUILifetime() 5

Table 6: Common Error Codes 6

Table 7: shortName values for known remoting protocols 10