IEC/TR 80001-2-5:2014-12 (E)

Application of risk management for IT-networks incorporating medical devices - Part 2-5: Application guidance - Guidance for distributed alarm systems

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 8
3 Terms and definitions 8
4 Functions of the distribution of ALARM CONDITIONS 16
4.1 General 16
4.2 SOURCES and their ALARM CONDITIONS 17
4.3 INTEGRATOR 17
4.4 COMMUNICATOR 17
4.5 MEDICAL IT-NETWORK 18
5 Types of systems for distributing ALARM CONDITIONS 18
5.1 General 18
5.2 DISTRIBUTED INFORMATION SYSTEM ABOUT ALARM CONDITIONS 19
5.3 DISTRIBUTED ALARM SYSTEM 19
5.4 DISTRIBUTED ALARM SYSTEM WITH OPERATOR CONFIRMATION 19
6 RISK MANAGEMENT 20
6.1 General explanation 20
6.2 Determining the RESPONSIBLE ORGANIZATION'S objective purpose 20
6.3 HAZARDS and HAZARDOUS SITUATIONS related to DIS, DAS and CDAS 21
6.4 Causes and resulting HAZARDOUS SITUATIONS 21
6.5 RISK CONTROL measures related to the integration of ALARM CONDITIONS 23
6.5.1 Technical RISK CONTROL measures implemented in equipment 23
6.5.2 Typical RISK CONTROL measures for implementation by the RESPONSIBLE ORGANIZATION 25
6.5.3 Organizational policies and procedures as RISK CONTROL measures for implementation by the RESPONSIBLE ORGANIZATION 26
Annex A (informative) Correspondence between the RISK CONTROL measures of this technical report and IEC 60601-1-8 28
Annex B (informative) Types of SOURCES 29
B.1 MEDICAL DEVICES 29
B.2 NURSE CALL SYSTEM 30
ANNEX C (informative) Applicability of types of system for the distribution of ALARM CONDITIONS 32
Annex D (informative) Scalability of types of system for the distribution of ALARM CONDITIONS 35
Bibliography 37
Index of defined terms used in this technical report 38

Figure 1 – Focus of this technical report 6
Figure 2 – Functions of a MEDICAL IT-NETWORK incorporating SOURCES, an INTEGRATOR and COMMUNICATORS to distribute ALARM CONDITIONS 7
Figure C.1 – Cascading structure of system for the distribution of ALARM CONDITIONS 32
Figure C.2 – Example for INTEGRATOR of a PATIENT monitor with central monitoring station to distribute ALARM CONDITIONS in a physically isolated IT-NETWORK in a CDAS 33
Figure C.3 – Example for INTEGRATOR of a PATIENT monitor to distribute ALARM CONDITIONS in a NURSE CALL SYSTEM, and via a PBX with handsets 34
Figure D.1 – Example hospital-wide DISTRIBUTED ALARM SYSTEM 36

Table 1 – General comparison of system properties for ALARM CONDITION integration 18
Table A.1 – Correspondence of the technical RISK CONTROL measures of this technical report for a CDAS and IEC 60601-1-8 for a DAS 28