ISO/IEC 14543-4-3:2015-09 (E)

Information technology - Home Electronic Systems (HES) architecture - Part 4-3: Application layer interface to lower communications layers for network enhanced control devices of HES Class 1

Contents

Page

FOREWORD 5
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviations 7
3.1 Terms and definitions 7
3.2 Abbreviations 9
4 Conformance 9
5 Services of the application layer 9
5.1 Positioning in communications layers 9
5.1.1 General 9
5.1.2 When using UDP in layer 4 and IP in layer 3 10
5.2 Service primitives of the application layer 10
5.2.1 General 10
5.2.2 NECD objects from the viewpoint of application software 11
5.2.3 Case 1: Obtaining the status of another node 11
5.2.4 Case 2: Controlling the functions of other nodes 12
5.2.5 Case 3: Notifying own node status to other nodes 13
6 Application layer protocol data unit (APDU) 15
6.1 Overview 15
6.2 NECD header (NHD) 16
6.2.1 Overview 16
6.2.2 NECD header 1 (NHD1) 16
6.2.3 NECD header 2 (NHD2) 17
6.3 Transaction ID (TID) 17
6.4 NECD data (NDATA) 17
6.5 NECD object (NOJ) 17
6.6 NECD Service (NSV) 18
6.6.1 Overview 18
6.6.2 Property value write service (no response required) [0x60, 0x50] 22
6.6.3 Property value write service (response required) [0x61, 0x71, 0x51] 22
6.6.4 Property value read service [0x62, 0x72, 0x52] 23
6.6.5 Property value write and read service [0x6E, 0x7E, 0x5E] 24
6.6.6 Property value notification service [0x63, 0x73, 0x53] 25
6.6.7 Property value notification (response required) [0x74, 0x7A] 26
6.7 Processing object property counters (OPC, OPCSet and OPCGet) 27
6.8 NECD property (NPC) 27
6.9 Property data counter (PDC) 28
6.10 NECD property value data (NDT) 28

7 Basic sequences 29
7.1 General 29
7.2 Basic sequences for object control 29
7.2.1 Overview 29
7.2.2 Basic sequences for object control in general 29
7.2.3 Basic sequences for service content 30
7.3 Basic sequences for node start-up 32
7.3.1 Overview 32
7.3.2 Basic sequence for NECD node start-up 32
8 NECD objects – Detailed specifications 33
8.1 General 33
8.2 Types of objects 33
8.2.1 Device objects 33
8.2.2 Node profile object 33
8.3 NECD property value data types 33
8.3.1 Overview 33
8.3.2 NECD property value range 34
8.3.3 Class-specific mandatory properties 34
8.3.4 Profiles obliged to have a status change announcement function 35
Bibliography 36

Figure 1 – Communications middleware 9
Figure 2 – Acquisition of status of another node (synchronous type) 11
Figure 3 – Acquisition of status of another node (asynchronous type) 12
Figure 4 – Objects seen from application software 12
Figure 5 – Method of controlling other nodes 13
Figure 6 – Objects seen from application software 13
Figure 7 – Method of notification to other nodes (synchronous type) 14
Figure 8 – Method of notification to other nodes (asynchronous type) 14
Figure 9 – Objects seen from application software 14
Figure 10 – Example of object configuration 15
Figure 11 – NECD frame format 16
Figure 12 – Bit specifications of NHD 1 17
Figure 13 – Detailed specifications of NHD 2 17
Figure 14 – Bit specifications of the NOJ code 18
Figure 15 – Bit specifications of the NSV code 18
Figure 16 – Sequence diagram for NSV transmission and reception 21
Figure 17 – NDATA configuration for property value write service (no response required) 22
Figure 18 – NDATA configuration for property value write service (response required) 23
Figure 19 – NDATA configuration for property value read service 24
Figure 20 – NDATA configuration for property value write and read service 25
Figure 21 – NDATA configuration for property value notification service 26
Figure 22 – NDATA configuration for property value notification (response required) service 27
Figure 23 – Processing target property counter for three requests 27

Figure 24 – NPC detailed specifications 28
Figure 25 – NPC code allocation 28
Figure 26 – Basic sequence when controlled object does not exist 29
Figure 27 – Basic sequence when controlled objects exist 30
Figure 28 – Basic request receiving sequence for NSV = 0x60 30
Figure 29 – Basic request receiving sequence for NSV = 0x6* 31
Figure 30 – Basic request receiving sequence for NSV = 0x63 31
Figure 31 – Basic property value notification sequence 32
Figure 32 – Basic sequence for NECD node start-up 32

Table 1 – List of NSV Codes for Requests 20
Table 2 – List of NSV codes for response/notification 20
Table 3 – List of NSV codes for “Response not possible” 21
Table 4 – Data types, data sizes and overflow / underflow codes 34